www.adeunis-rf.com







1 to 8 keys 1-way and 2-ways radio remote control

The ARF18 low cost remote controls enable wireless control of **1 to 24 digital states (by simultaneously pressing 2 keys or switch)** over a distance of **300m**.

They are available in **one-way or two-ways versions** on respectively 433.92 or 869.52MHz and are **approved according** to the European directive RTTE EN 300-220/EN 301-489.

Security of transmission is ensured by means of a proprietary rotating code and a unique serial number.

They are associated with a complete range of RS232 or USB serial decoder & serial link, 4 relays or 4 binary outputs receivers.

In the **two-ways version**, the return acknowledgement of the sent command validates the correct transmission of the order and thus provides a maximum level of security for applications involving access control, alarms...

More generally, these products cover applications ranging from **simple domestic remote control to autonomous control of tertiary or industrial equipment,** in sectors of activity such as home automation, systems automation, industrial automation...

Specifications

Remote control

Frequency

Radiated RF power Temperature range

- Modulation
- Number of keys

OEM receiver - asynchronous link

Power supply (Vcc)

- Consumption in receipt
- Sensitivity
- Outputs

4 relays receiver

- Power supply
- Consumption
- Switching capacity
- Relays

Serial decoder

- Serial ports
- Format
- Serial link rate
- Power supply

DemoKit - Integration kit including : demoboard, module, remote control, RS232 cable, power supply

- Evaluate the products
- Perform RF measurements
- Develop a prototype

Your distributor

1-way version 433.92MHz 1mW -30/+70°C ASK 1 to 8

3.3V nominal 15mA -104dBm Serial interface level 0/VCC 4 binary outputs

15 to 30VDC 30mA open relays (130mA closed) 230VAC max 10A 3 NO + 1 NO/NC

RS232 or USB 8 bits, no parity, 1 stop configuration through AT commands 2.4 to 115.2kBps 8 to 30VDC **2-ways version** 869.525MHz 6mW -20/+70°C FSK 1 to 4

2.7 to 3.6V nominal 15mA -104dBm Serial interface level 0/VCC 4 binary outputs



One-wa

ARF72

ARF72

ARF73

ARF72

ARF72

ARF74

Part Numbers

Remote control OEM receiver 4 relays receiver - IP65 box RS232 serial decoder - IP65 box USB serial decoder - IP65 box DemoKit

У	Two-way
91X*	ARF729
93A	ARF729
41B	-
63K	
63S	
395	ARF743

* X=index A/B/C/D/R = 1/2/3/4/8 keys ** X=index A/B/C/D = 1/2/3/4 keys

Adeunis

7X*>

89M

283 rue Louis Néel-Parc technologique Pré Roux 38920 CROLLES - FRANCE Tel (33) 04 76 92 07 77 - Fax (33) 04 76 08 97 46 Email: arf@adeunis-rf.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for adeunis manufacturer:

Other Similar products are found below :

ARF7208A ARF7044A