3919545



V 450 HR

Ni-MH

Data Sheet

↓ ↓ h	- +

Type Number:	55945	
System:	Nickel Metal Hydride / KOH Electrolyte	
UL Recognition:	pending	
Nominal Voltage [V]:	1,2	
Typical Capacity C [mAh]:	460	
Nominal Capacity C [mAh]:	450	
at 0.2 CA / 1.00 V		
Weight, approx [g]:	12,5	
Coding:	Manufacturing 5 digit code (123 = day/4 = year/5 = vers)	
Temperature Ranges [°C]:	min. max.	
Storage:	-20 45	
Discharge:	-20 65	
Charge:	0 65	
Dimensions [mm]:	min. max.	
Length [l]:	23,9 24,1	
Width Facing [w]: Height [h]:	33,9 34,1 5 5,4	
	5 5,4	
Charging Method: Normal Charging:	45 mA for 14-16 h	
Accelerated Charging (20°C):		
Fast Charging :		
Trickle Charging :	13,5 mA	
Overcharge (20°C):	mA continuous	
	mA 1 year	
Charge Retention [%] at 20°C:	80	
Capacity available after 1 month storage at 20 °C		
Internal Resistance [Ohm]:		
at charged cells, 20 °C, DC: 0.5 CA/5 CA, (IEC 285)		
Impedance [Ohm]:	0,02	
at charged cells, 20 °C, AC: 1 kł	Hz, (IEC 285)	
Typical Capacities [mAh]:	110	
at 1 CA / 1.0 V	410	
at 3 CA / 0,90 V at 5 CA / 0.80 V	350 300	
Max. Discharge Current (cont.)[mA]:		
Life Expectancy (typical):	2200	
	1000 Cycles	
Trickle Charge:	(20°C)	
Trickle Charge:	(45°C)	

* (-dV = 5-10 mV/cell;)dT/dt = 0.7 ° C/min)

VARTA Gerätebatterie GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst Tel.: (+49) 7961/83-0, Telefax: (+49) 7961/83-553

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for varta manufacturer:

Other Similar products are found below :

56456 702 099 18750 4114 210 501 4610 726 406 4122 210 511 LCD-CHARGER + 4XAA 2400MAH 449915B 4607 726 406 55171403014 55625603059 55615602940 4112101411 4 022 211 111 4 106 101 436 4 020 211 111 MINI CHARGER + 2XAA 2100MAH MINI-CHARGER 17730 LCD-SMART-CHARGER 414086X POCKET-CHARGER + 4XAA 2100MAH 458980A LCD MULTI CHARGER CG511-150-PB EE UNIVERSAL CHARGER CG401D-050-PB CG511-050-PB CU303-018-PB 413675G CG381D-G-100-PB CU202-030-PB 55615603059 CG381D-G-150-PB CG481G-050-PB CU303-030-PB CG511D-030-PB CA317-PB CU201G-B-030-PB 095668F 4600 726 406 CA418-PB CG481G-030-PB CG511D-100-PB CG511-030-PB CG511D-150-PB CG381D-G-050-PB CU302-030-PB CG341-030-PB CU201G-B-050-PB CA089-PB