



852-112 has 8 ports with each port featuring Auto-negotiation and Auto MDI/MDI-X detection. Existing 10Mbps networks can now be upgraded effortlessly to higher speed 100Mbps Fast ETHERNET networks. The 852-112 8-port density can be used to create multiple segments to alleviate client congestion and provide dedicated bandwidth to each user node. The 852-112 is a cost-effective solution to keep up with the constant demands for emerging IP-based industry communication needs. The switch can be easily configured and installed and is also ideally suited for small to medium-sized networks.

Features:

- 8-port 10/100 Mbps Auto-negotiation ETHERNET ports
- Comprehensive front-panel diagnostic LEDs
- Supports Auto-MDI/MDI-X
- Full/half-duplex transfer modes for each port
- Wire speed reception and transmission
- Store-and-forward switching method
- Integrated address Look-Up Engine, supports 2K absolute MAC addresses
- Supports surge protection
- IEEE 802.3x flow control for full duplex
- Supports DIN 35 rail

Description	Item no.	Pack. unit	Technical Data																								
8-Port 100BASE-TX Industrial Eco Switch	852-112	1	<table border="1"> <tr> <td>Ports</td> <td>8 x 10/100Base-TX (RJ-45)</td> </tr> <tr> <td>Standards</td> <td>IEEE 802.3 10Base-T; IEEE 802.3u 100Base-TX/FX; IEEE 802.3x Flow Control</td> </tr> <tr> <td>Topology</td> <td>Star</td> </tr> <tr> <td>LED</td> <td>each device: 1 x Power (PWR), green; each port: 1 x Link/Activity (LNK/ACT), green; 1 x Speed (100 Mbps), green</td> </tr> <tr> <td>Supply voltage</td> <td>DC 18 V ... 30 V</td> </tr> <tr> <td>Energy consumption max.</td> <td>3 W</td> </tr> <tr> <td>Operating temperature</td> <td>0 °C ... +60 °C</td> </tr> <tr> <td>Storage temperature</td> <td>-20 °C ... +80 °C</td> </tr> <tr> <td>Relative air humidity (no condensation)</td> <td>95 %</td> </tr> <tr> <td>Dimensions (mm) W x H x L</td> <td>109.2 x 23.4 x 73.8</td> </tr> <tr> <td>Mounting</td> <td>Height from upper-edge of DIN 35 rail DIN 35 rail</td> </tr> <tr> <td>Weight</td> <td>415 g</td> </tr> </table>	Ports	8 x 10/100Base-TX (RJ-45)	Standards	IEEE 802.3 10Base-T; IEEE 802.3u 100Base-TX/FX; IEEE 802.3x Flow Control	Topology	Star	LED	each device: 1 x Power (PWR), green; each port: 1 x Link/Activity (LNK/ACT), green; 1 x Speed (100 Mbps), green	Supply voltage	DC 18 V ... 30 V	Energy consumption max.	3 W	Operating temperature	0 °C ... +60 °C	Storage temperature	-20 °C ... +80 °C	Relative air humidity (no condensation)	95 %	Dimensions (mm) W x H x L	109.2 x 23.4 x 73.8	Mounting	Height from upper-edge of DIN 35 rail DIN 35 rail	Weight	415 g
Ports	8 x 10/100Base-TX (RJ-45)																										
Standards	IEEE 802.3 10Base-T; IEEE 802.3u 100Base-TX/FX; IEEE 802.3x Flow Control																										
Topology	Star																										
LED	each device: 1 x Power (PWR), green; each port: 1 x Link/Activity (LNK/ACT), green; 1 x Speed (100 Mbps), green																										
Supply voltage	DC 18 V ... 30 V																										
Energy consumption max.	3 W																										
Operating temperature	0 °C ... +60 °C																										
Storage temperature	-20 °C ... +80 °C																										
Relative air humidity (no condensation)	95 %																										
Dimensions (mm) W x H x L	109.2 x 23.4 x 73.8																										
Mounting	Height from upper-edge of DIN 35 rail DIN 35 rail																										
Weight	415 g																										

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Modules](#) category:

Click to view products by [Wago](#) manufacturer:

Other Similar products are found below :

[1026937](#) [1026932](#) [M38510/00302BCA](#) [70001610](#) [70001634](#) [850-15633](#) [PD-AS-951/12-24](#) [GX-OC1601](#) [1402407](#) [I210T1](#) [I350T4V2](#)
[SBL2EX](#) [SL170115](#) [GX-OD1612](#) [CPTS-4R4E-R](#) [TDKEZW3](#) [I350F2](#) [I350F2BLK](#) [I350T2V2](#) [V23993-USB1029A](#) [100-POE4](#) [105FX-ST](#)
[105TX-SL](#) [SEG305-T](#) [70001992](#) [70001993](#) [708TX](#) [854-19720](#) [I350T4V2BLK](#) [I350T2V2BLK](#) [I210T1BLK](#) [PD-OUT/MBK/S](#) [SX-BR-](#)
[4600WAN2-US](#) [W4S105C](#) [X710DA4FHBLK](#) [I350T2V2BLK](#) [936714](#) [GX-ID1611](#) [3G8F7-DRM21-E](#) [EKI-2525I-BE](#)
[BCM53426A0KFSBG](#) [PCM-24R2GL-AE](#) [96NIC-1G4P-PE-IN2](#) [0.70001777](#) [BCM53402A0KFSBG](#) [105FXE-SC-15-POE](#) [PD-OUT/MBK/G](#)
[856-15410](#) [X520QDA1](#) [BCM84794A1KFSBG](#) [X520DA2OCP](#)