

#### **Electromechanical Terminal Blocks**




## Porcelain terminal blocks

### **SERIES 560**

## Explosion-proof modular flat screw connectors





#### **FEATURES**

Series 560 ceramic terminal blocks offer a variety of models for explosion-proof and high temperature applications.

These terminals comprise of a glazed steatite mount and two riveted flat-type screw terminals secured to prevent them from twisting, similar to DIN 41000, with binding clip C or D and spring washers B DIN 127. The blocks may either be used rail mounted or independently. The base has a longitudinal slot at the bottom for non-twist securing on mounting rails 16mm x 3mm (0.63" x 0.12"). The surfaces next to the screw-fixing hole can be used for marking purposes.

Recommended mounting hardware: M4 pan head screw.

| Approvals                             | <i>7</i> .7         | <b>®</b>            |  |
|---------------------------------------|---------------------|---------------------|--|
| Nominal Cross-Section mm <sup>2</sup> | 20-12<br>AWG<br>20A | 20-12<br>AWG<br>25A |  |
| Voltage Rating V                      | 300                 | 600                 |  |

| TECHNICAL DETAILS  |  |
|--------------------|--|
| Formers:           | Steatite KER 220, DIN 40685, colour white    |
| Inserts:           | brass, nickel plated                         |
| Screws:            | M4 steel, zinc plated, blue passivated       |
| Lock washer:       | steel, zinc plated, blue passivated          |
| Binding clip:      | steel, zinc plated, blue passivated          |
| Temp. upper limit: | as per EX approvals: 40° C (104° F)          |
|                    | physical limit of materials: 240° C (464° F) |
| Current rating:    | see approvals                                |
| Voltage rating:    | see approvals                                |
| Conductor size:    | 2.5mm <sup>2</sup>                           |
| Stripping length:  | 8mm <sup>2</sup>                             |
|                    |  |

|              | EX APPROVED TYPES                      |  |  |
|--------------|--|--|--|
|              | Type designation                       |  |  |
| Part number: | 560-EN-K4CF:                           | without groove, with wire clip C & spring washer |  |
| Part number: | 560-EN-K4DF:                           | without groove, with wire clip D & spring washer |  |
|              | NOT EX APPROVED TYPES Type designation |  |  |
| Part number: | 560-R4:                                | with groove                                      |  |
| Part number: | 560-R4F:                               | with groove & spring washer                      |  |
| Part number: | 560-K4C:                               | without groove, with wire clip C                 |  |
| Part number: | 560-K4CF:                              | without groove, with wire clip C & spring washer |  |
| Part number: | 560-K4DF:                              | without groove, with wire clip D & spring washer |  |
| Part number: | 560-K4DF - V2A:                        | stainless steel version of the 560-K4DF.         |  |
|              |  | Temperature resistant up to 500° C / 940° F      |  |





**\*** 



# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for metway manufacturer:

Other Similar products are found below:

560-K4CF 503SI03E 98001RZ03SKB 5001235 1003SI03E