



24V

ALF2401


PRATICAL : ON/OFF switch.

- Power-on indicator.



PRECISE : Output ripple < 3mV rms.

- Output voltage adjustable from 20 to 30V.

PROTECTED : against Short circuit.**RESISTANT TO SHOCK****30 WATTS**

24 V

1,25 A

**Specifications****Voltage**

- Floating outputs on 4 mm safety sockets.
- Output voltage : adjustable from 20 to 30V linearly. Delivered to 24V \pm 1%
- Regulation : < 20mV for a load change from 0 to 100%
< 5mV for a line change from 190 to 264V.
- Ripple : < 3mV rms including:
< 3mV peak to peak of the switching signal
< 4mV peak to peak of the signal at 100 Hz
< 15mV peak to peak of switching spikes
- Dynamic regulation : <0,5% for a load change from 10 to 90%
- Indicator : green power-on LED indicator.

Current

- Max I : 1,5A to 20V
1,25A to 24V
1A to 30V

Power

- Max output power : 30W.
- Efficiency : >82% at the full power (30W in output)

Protection

- Short circuit protection, by current regulation.
- Transformer primary overcurrent protection, by fuse.
- Against transient pulse on the primary by varistor.

Other specifications

- Safety : Class II, Safety Extra Low Voltage (SELV) according to EN 61010-1.
- EMC : Complies with EN 61326-1, performance criteria B, and EN 55011, ISM Group I, Class B.
- Protection level : IP 30.
- Input voltage : 190 to 264 Volts, 50 / 60 Hz.
- Mains input : double insulation 2 poles cable.
- Power consumption : 35 W max.
- ON/OFF control : toggle switch
- Dielectric strength : 3000 Vac between input and output.
- Presentation : polycarbonate case screenprinted.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bench Top Power Supplies](#) category:

Click to view products by [ELC](#) manufacturer:

Other Similar products are found below :

[NL200](#) [PR20](#) [ZUPNC403](#) [Z60-7-L-U](#) [ZUPNC402](#) [GDM-8342](#) [GPIB](#) [PSW 250-4.5](#) [CPX200DP](#) [AX-8450A](#) [TPM-3003](#) [HMP2020](#)
[HMP2030](#) [HMP4040](#) [1320](#) [1350](#) [UT804](#) [1405](#) [1410](#) [1513](#) [1514](#) [1513](#) [1550](#) [1651A](#) [1665](#) [1666](#) [1667](#) [SDP-2405-000G](#) [1673](#) [1693](#) [1694](#)
[MX100TP](#) [1737](#) [1739](#) [1762](#) [1788](#) [TPM-3005](#) [1900](#) [1902B](#) [9174B](#) [GDM-8245](#) [GDM-8255A](#) [GDM-8341](#) [PSW 160-7.2](#) [PSW 30-36](#) [PSW](#)
[80-13.5](#) [Z10-20-LAN-U](#) [PSW 30-72](#) [QL355P SII](#) [Z36-6-LAN-U](#) [HCS-3400-USB](#)