

## T50RSF9C2



**Article Number:** 111-85789

**Push Mount Tie, 8.3" Long, 50lb Tensile, Panel Thickness .25"- .28", PA66, Natural, 100/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T50RSF9C2

**Type** T50RSF(U)

**Color** Natural (NA)

- Features and Benefits**
- Push Mount design creates quick and easy mounting for installers.
  - Push mount style creates low insertion and high extraction force.
  - Ties "clicks" into place upon final installation signaling installer insertion is complete.

**Product Description** Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

**Short Description** Push Mount Tie, 8.3" Long, 50lb Tensile, Panel Thickness .25"- .28", PA66, Natural, 100/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225 N

**Length L (Imperial)** 8.3 "

**Length L (Metric)** 210.0 mm

**Fixation Method** Arrowhead

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.19 "

**Width W (Metric)** 4.7 mm

**Height H (Imperial)** 0.3 "

**Height H (Metric)** 7.5 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.6 mm

**Bundle Diameter Max. (Imperial)** 1.7 "

**Bundle Diameter Max. (Metric)** 44.0 mm

**Panel Thickness Max. (Imperial)** 0.14 "

**Panel Thickness Max. (Metric)** 3.5 mm

**Panel Thickness Min. (Imperial)** 0.04 "

**Panel Thickness Min. (Metric)** 1.0 mm

**Mounting Hole Diameter D (Imperial)** 0.25 - 0.28 "

**Mounting Hole Diameter D (Metric)** 6.4 - 7.1 mm

Mounting Hole Diameter D Min. 0.25 "  
(Imperial)

Mounting Hole Diameter D Max. 0.28 "  
(Imperial)

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. 7.1 mm  
(Metric)

Mounting Hole Diameter D Min. (Metric) 6.4 mm

Thickness T (Metric) 1.2 mm

## Logistics and Packaging

---

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 5000

Weight (Metric) 1.5 kg

## Material and Specifications

---

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

Certification/Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)