

## T50L0UVC2



**Article Number:** 112-05460

**Standard Cable Tie, 15.35" Long, 50lb Tensile Strength, PA66UV, Black, 100/pkg**



Download spec sheet

### Base Data

<b>Local Order Number</b>	T50L0UVC2
<b>Type</b>	T50L
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures .</li> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
<b>Product Description</b>	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	Standard Cable Tie, 15.35" Long, 50lb Tensile Strength, PA66UV, Black, 100/pkg

### Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	50.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	225.0 N
<b>Length L (Imperial)</b>	15.35 "
<b>Length L (Metric)</b>	390.0 mm
<b>Fixation Method</b>	None
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18 "
<b>Width W (Metric)</b>	4.7 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.06 "
<b>Bundle Diameter Min. (Metric)</b>	1.5 mm
<b>Bundle Diameter Max. (Imperial)</b>	4.3 "
<b>Bundle Diameter Max. (Metric)</b>	110.0 mm
<b>Thickness T (Imperial)</b>	0.05 "
<b>Thickness T (Metric)</b>	1.2 mm

### Logistics and Packaging

<b>Quantity Per</b>	pieces
<b>Package Quantity (Metric)</b>	100 Pieces

**Carton Quantity** 5000

**Weight (Metric)** 2.7 kg

## Material and Specifications

---

**Material** Polyamide 6.6 UV-resistant (PA66UV)

**Material Shortcut** PA66UV

**US MILSPEC** MS3367-2-0

**Flammability** UL94 V2

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**Certification/Specification** BACS38K  
MS3367  
UL-ZODZ2.E64139  
Cage Code 53421  
SAE - AS33671

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** No

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)