



Part Number: MMPSC 130/30


Proximity Switch - Reed Switch based

Rectangular - Change Over Contacts - Suggested Magnet: MMPSM

Product Data Sheet

PICTURE

DIMENSIONS



Drawings not to scale
All dimensions in mm(inches) nominal

Applications Include

- Position and limit sensing.
- Linear actuators .
- Security system switch.
- Door Switch.

Options

- Also available in all Black.
- White economy version available.
- Left and Right hand version available.
- Custom cable lengths, strip lengths, cable types, terminations.
- If you do not see what you need, jusk ask, as there is a strong possibility we can do it!

✓ RoHS Compliant

SPECIFICATION	
Contact Form / Style	Change - Over
Switching Capacity (Resistive)	5 W/VA Max.
Switching Voltage	100 VAC Max.
Switching Current	0.5 A. Max.
Carry Current	1.0 A. Max.
Breakdown Voltage	200 VDC Min.
Contact Resitance	150 mOhms Max.
Switching Distance	8 mm Min.
Operating Temperature Range	-20°C +85°C
Storage temperature	-25°C +90°C
Case Material	Blue Nylon 66
Cable	3 x Round 0.14mm² PVC covered Grey and insulated Brown / White / Green

Did you know we also sell?













Rev. No.Revision NoteDateSignature2Datasheet Redesign28-07-06LG



As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by Comus manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 9221350022 980659-1 QT-12 E2EX10D1NN E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2E-X3D1-N 10M E2E-X4MD1-G E2FMX1R5D12M E2K-F10MC1 5M EI1204TBOSL-6 EI5515NPAP BSA-08-25-08 IC08ANC15PO-K IMM2582C 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0 25.523.3253.0 9151710023 922FS1.5C-A4P-Z774 SC606ABV0S30 SM952A126100LE A1220EUA-T F3S-A162-U CL18 QT-08L 34.110.0010.0 TL-C2MF1-M3-E4 IMM32188C IS2 IS31SE5000-UTLS2-TR 34.110.0021.0 34.110.0022.0 CA150-120VACDC VM18VA3000Q XS508BSCBL2 XS512BLNAM12 XS512BLNBL2 XS512BLPAL5 XS518B1MBU20