

Specifications	
Number of Contacts	6
Application	Ruggedized Commercial / Military
Overall Diameter	.828 in
Overall Length	1.859 in
Standard	MIL-C-55116
Alternate P/N	M55116/4 U-229 Type
Connector Style	Plug
Contact Types	Solder
Strain Relief	Wire
Shell Material	Stainless Steel, 303, Passivated
Mating	Bayonet Coupling
Mating Cycles	3000
Temperature	-55 to 85 °C
Insert Material	Thermoset Plastic
Contact Material	Gold-plated Brass / Silver-plated BeCu (Springs)
Current Rating	0.5 A
Voltage Rating Maximum	60 V
Contact Depression	1.25-1.75 lbs per contact
Contact Resistance Maximum	.050 O
Insulation Resistance	1000 megaohms min, except for connectors unmated after immersion test shall not be less than 100 megaohms
Dielectric Withstanding Voltage; Sea Level (RMV)	500 V
Water Immersion	6 feet of water up to 48 hours (mated and unmated)

Request Information

ogies, Incorporated

rd, CT 06902 ax: 203-324-7623 Email: <u>salesinfo@nexus.com</u> Privacy Policy Site Map Catalog Index

WWW.NEXUS.COM



ogies, Incorporated, All Rights Reserved

Site Created by Thomas Web Solutions and powered by Navigator Platform

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for XLR Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below :

707-0300 8800235 91101181024 91201231 91214571 A3F01 A3M01 QGP3F HA16PRQ-3SE(71) AA3FL AAA4FWZ AAA4MWZ AC3-MIC AC4-MIC AC5FPZB AC6AFDZV AC7FDZB D4FB DE4MW DHNF-BAG E3MBAUSW NA2FP-UW NA3MP-UW NC3FBHR1-0 NC3FD-H-0 NC3FK-V NC3FX-1 NC3FXY-B NC3MDM3-H-B NC3MK-V NC3MXY NC4FD-LX-0 NC5FX-HD-B NC6FSXX-BAG NC6MD-LX-BAG NC6MSX-BAG RT3FC-B-W-D 91210071096 SL05 99.265.0400.0 A3F04 AC3FG AC3MMG AC4-FCP AC4FPZ AQG4F 2504FP 30-498-2 R6MZ CXX-15