

## T250XL0X2



**Article Number:** 111-25200

**Heavy Duty Cable Tie, 40.6" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T250XL0X2

**Type** T250XL

**Color** Black (BK)

**Features and Benefits**

- Heavy duty design to offer higher tensile strength.
- Buckle feature on head allows excess strap to be tucked away after installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Heavy Duty Cable Tie, 40.6" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 250.0 lbs

**Minimum Tensile Strength (Metric)** 1115.0 N

**Length L (Imperial)** 40.6 "

**Length L (Metric)** 1030.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.49 "

**Width W (Metric)** 12.5 mm

**Bundle Diameter Min. (Imperial)** 0.47 "

**Bundle Diameter Min. (Metric)** 12.0 mm

**Bundle Diameter Max. (Imperial)** 12.0 "

**Bundle Diameter Max. (Metric)** 305.0 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 25 Pieces

**Carton Quantity** 250

**Weight (Metric)** 15.436 kg

### Material and Specifications

**Material** Polyamide 6.6 (PA66)  
**Material Shortcut** PA66  
**Flammability** UL94 V2  
**Halogenfree** Yes  
**Operating Temperature** -40°F to +185°F (-40°C to +85°C)  
**ROHS Compliant** Yes  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)