



**Led Signalleuchten Einbaudurchmesser 6 mm**  
**Led Indicators Body diameter 6 mm**

**Zweifarbige, mit Innenreflektor**  
**Duo Led, with interior reflector**

Bestell-Nr. Part No.	Farbe Colour	V <sub>OP</sub> +10% (V)	I <sub>OP max.</sub> (mA)	V <sub>F</sub> (V)	I <sub>V typ.</sub> (mcd) *I <sub>F</sub> = 20mA	I <sub>F max.</sub> (mA)	Abb. Illu.	Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	19030-A	A
1903*004	Super red/ Green			2,0/2,2 2,2/2,8	*14/22	30	A	  		
1903*005	Super red/ Yellow			2,0/2,2 2,2/2,8	*14/14	30	A			
1903*006	Green/ Yellow			2,0/2,2 2,2/2,8	*22/14	30	A			
1903*054	Super red/ Green			2,0/2,2 2,2/2,8	*14/22	30	B			
1903*055	Super red/ Yellow			2,0/2,2 2,2/2,8	*14/14	30	B			
1903*056	Green/ Yellow			2,0/2,2 2,2/2,8	*22/14	30	B			
1903*154	Super red/ Green	6	30		19/34		B			
1903*155	Super red/ Yellow	6	30		19/20		B			
1903*156	Green/ Yellow	6	30		34/20		B			
1903*254	Super red/ Green	12	30		19/34		B			
1903*255	Super red/ Yellow	12	30		19/20		B			
1903*256	Green/ Yellow	12	30		34/20		B			
1903*354	Super red/ Green	24	18		13/20		B			
1903*355	Super red/ Yellow	24	18		13/13		B			
1903*356	Green/ Yellow	24	18		20/13		B			

Arbeits-temperatur (T<sub>OP</sub>): -55°C - +70°C  
 Lagertemperatur (T<sub>STG</sub>): -55°C - +100°C

\* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0      Schwarzchrom = 1

Beispiel:      19030004 super rot / grün mit Glanzchrom  
                  19031004 super rot / grün mit Schwarzchrom

Operating temperature (T<sub>OP</sub>): -55°C - +70°C  
 Storage temperature (T<sub>STG</sub>): -55°C - +100°C

\* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0      Black chrome = 1

Example:      19030004 super red / green with bright chrome  
                  19031004 super red / green with black chrome

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Panel Mount Indicators](#) category:*

*Click to view products by [CML](#) manufacturer:*

Other Similar products are found below :

[607-1312-310F](#) [607-3232-140F](#) [6091M1-24V](#) [6091M5-24V](#) [6091M7-24V](#) [821-0331-503](#) [FL2870C8R](#) [FL2950WL7B](#) [FL589WL8R](#)  
[Q6P3BXXB12E](#) [H8630FBBA3](#) [MPC5ADW6.0](#) [DX1091GN](#) [NL177WL3G](#) [NL276C3G](#) [NL2950BWL3G](#) [NL2950CWL2R](#) [NL589WL2R](#)  
[NL67C3G](#) [NL67C3R](#) [2191L1-12V](#) [PB22SIOL0RG](#) [PB22SPPM41R](#) [PB22SPPM61R](#) [LE177C5B](#) [LH1048BSWL3702](#) [LH1048BWL3702](#)  
[LH382A](#) [LHM62B](#) [SSI-LXH387USBD-150](#) [SSI-LXH9ZIC40587](#) [SSP-LXS110818BA](#) [FL2950BWL7R](#) [FL2950WL7R](#) [FL2951WL8G](#)  
[FL2951WL8R](#) [FL589C7R](#) [FL67C7R](#) [FL67WL8G](#) [2191QU7-24V](#) [2191U1-12V](#) [2191U5-12V](#) [2191U5-6V](#) [2191U7-12V](#) [249-4167-3734-504F](#) [Q6P5BXXG02E](#) [3990A7](#) [5110F3-12V](#) [MPC5BCW18.0](#) [556-1237-801F](#)