



ALPHA & OMEGA
SEMICONDUCTOR

AOTF4185
40V P-Channel MOSFET

General Description

The AOTF4185 combines advanced trench MOSFET - 40V technology with a low resistance package to provide extremely low $R_{DS(ON)}$. This device is ideal for load switch and battery protection applications.

Product Summary


V_{DS}	-40V
I_D (at $V_{GS}=-10V$)	-34A
$R_{DS(ON)}$ (at $V_{GS}=-10V$)	< 16m Ω
$R_{DS(ON)}$ (at $V_{GS}=-4.5V$)	< 20m Ω

100% UIS Tested
100% R_g Tested





TO220F

Top View



Bottom View



Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	V_{DS}	-40	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ^A	I_D	-34	A
$T_C=100^\circ\text{C}$		-27	
Pulsed Drain Current ^C	I_{DM}	-100	A
Avalanche Current ^C	I_{AS}, I_{AR}	-42	A
Avalanche energy $L=0.1\text{mH}$ ^C	E_{AS}, E_{AR}	88	mJ
Power Dissipation ^B	P_D	33	W
$T_C=100^\circ\text{C}$		16	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 175	°C

Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^{AD}	$R_{\theta JA}$	10	13	°C/W
Maximum Junction-to-Case	Steady-State $R_{\theta JC}$	3	4.5	°C/W

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	$I_D=-250\mu\text{A}, V_{GS}=0\text{V}$	-40			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=-40\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$			-1 -5	μA
I_{GSS}	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}= \pm 20\text{V}$			± 100	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	-1.7	-1.85	-2.5	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=-10\text{V}, V_{DS}=-5\text{V}$	-120			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=-10\text{V}, I_D=-20\text{A}$ $T_J=125^\circ\text{C}$	13	16		$\text{m}\Omega$
		$V_{GS}=-4.5\text{V}, I_D=-15\text{A}$	19	23		
g_{FS}	Forward Transconductance	$V_{DS}=-5\text{V}, I_D=-20\text{A}$	16	20		$\text{m}\Omega$
V_{SD}	Diode Forward Voltage	$I_S=-1\text{A}, V_{GS}=0\text{V}$	-0.72	-1		V
I_{S}	Maximum Body-Diode Continuous Current				-20	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=-20\text{V}, f=1\text{MHz}$		2550		pF
C_{oss}	Output Capacitance		280			pF
C_{rss}	Reverse Transfer Capacitance		190			pF
R_g	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$	2.5	4	6	Ω
SWITCHING PARAMETERS						
$Q_{\text{g}(10\text{V})}$	Total Gate Charge	$V_{GS}=-10\text{V}, V_{DS}=-20\text{V}, I_D=-20\text{A}$		42	55	nC
$Q_{\text{g}(4.5\text{V})}$	Total Gate Charge		18.6			nC
Q_{gs}	Gate Source Charge		7			nC
Q_{gd}	Gate Drain Charge		8.6			nC
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{GS}=-10\text{V}, V_{DS}=-20\text{V}, R_L=1.0\Omega, R_{\text{GEN}}=3\Omega$	9.4			ns
t_r	Turn-On Rise Time		20			ns
$t_{\text{D(off)}}$	Turn-Off Delay Time		55			ns
t_f	Turn-Off Fall Time		30			ns
t_{rr}	Body Diode Reverse Recovery Time	$I_F=-20\text{A}, dI/dt=500\text{A}/\mu\text{s}$	25	33		ns
Q_{rr}	Body Diode Reverse Recovery Charge	$I_F=-20\text{A}, dI/dt=500\text{A}/\mu\text{s}$	75			nC

A. The value of $R_{\theta JA}$ is measured with the device in a still air environment with $T_A=25^\circ\text{ C}$.

B. The power dissipation P_D is based on $T_{J(\text{MAX})}=175^\circ\text{ C}$, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(\text{MAX})}=175^\circ\text{ C}$.







D. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.






E. The static characteristics in Figures 1 to 6 are obtained using $<300\mu\text{s}$ pulses, duty cycle 0.5% max.




F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(\text{MAX})}=175^\circ\text{ C}$.





G. The maximum current rating is limited by bond-wires.

COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

Fig 1: On-Region Characteristics (Note E)

Figure 2: Transfer Characteristics (Note E)

Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)

Figure 4: On-Resistance vs. Junction Temperature (Note E)

Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)

Figure 6: Body-Diode Characteristics (Note E)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

Figure 7: Gate-Charge Characteristics

Figure 8: Capacitance Characteristics

Figure 9: Maximum Forward Biased Safe Operating Area (Note F)

Figure 10: Single Pulse Power Rating Junction-to-Case (Note F)

Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

Figure 12: Power De-rating (Note B)

Figure 13: Current De-rating (Note B)

Figure 14: Single Pulse Avalanche capability

Gate Charge Test Circuit & Waveform

Resistive Switching Test Circuit & Waveforms

Unclamped Inductive Switching (UIS) Test Circuit & Waveforms

Diode Recovery Test Circuit & Waveforms


X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET category:

Click to view products by Alpha & Omega manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)