



**ALPHA & OMEGA**  
SEMICONDUCTOR

**AON7423**


**20V P-Channel MOSFET**

### General Description



The AON7423 combines advanced trench MOSFET technology with a low resistance package to provide extremely low  $R_{DS(ON)}$ . This device is ideal for load switch and battery protection applications.

### Product Summary

$V_{DS}$	-20V
$I_D$ (at $V_{GS}=-4.5V$ )	-50A
$R_{DS(ON)}$ (at $V_{GS}=-4.5V$ )	< 5mΩ
$R_{DS(ON)}$ (at $V_{GS}=-2.5V$ )	< 6.5mΩ
$R_{DS(ON)}$ (at $V_{GS}=-1.8V$ )	< 8.5mΩ
$R_{DS(ON)}$ (at $V_{GS}=-1.5V$ )	< 11mΩ
100% UIS Tested	
100% $R_g$ Tested	



Top View



### Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	-20	V
Gate-Source Voltage	$V_{GS}$	$\pm 8$	V
Continuous Drain Current <sup>G</sup>	$I_D$	-50	A
$T_C=100^\circ\text{C}$		-39	
Pulsed Drain Current <sup>C</sup>	$I_{DM}$	-200	
Continuous Drain Current	$I_{DSM}$	-28	A
$T_A=70^\circ\text{C}$		-22.5	
Avalanche Current <sup>C</sup>	$I_{AS}, I_{AR}$	60	A
Avalanche energy $L=0.1\text{mH}$ <sup>C</sup>	$E_{AS}, E_{AR}$	180	mJ
Power Dissipation <sup>B</sup>	$P_D$	83	W
$T_C=100^\circ\text{C}$		33	
Power Dissipation <sup>A</sup>	$P_{DSM}$	6.2	W
$T_A=70^\circ\text{C}$		4	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	°C

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	16	20	°C/W
Maximum Junction-to-Ambient <sup>A,D</sup>		45	55	°C/W
Maximum Junction-to-Case	$R_{\theta JC}$	1.1	1.5	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=-250\mu\text{A}$ , $V_{GS}=0\text{V}$	-20			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=-20\text{V}$ , $V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$			-1	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Body leakage current	$V_{DS}=0\text{V}$ , $V_{GS}=\pm 8\text{V}$			$\pm 100$	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$ $I_D=-250\mu\text{A}$	-0.2	-0.5	-0.9	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=-4.5\text{V}$ , $V_{DS}=-5\text{V}$	-200			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=-4.5\text{V}$ , $I_D=-20\text{A}$ $T_J=125^\circ\text{C}$	3.95	5		$\text{m}\Omega$
		$V_{GS}=-2.5\text{V}$ , $I_D=-20\text{A}$	4.9	6.5		$\text{m}\Omega$
		$V_{GS}=-1.8\text{V}$ , $I_D=-20\text{A}$	6.1	8.5		$\text{m}\Omega$
		$V_{GS}=-1.5\text{V}$ , $I_D=-20\text{A}$	7.7	11		$\text{m}\Omega$
$g_{\text{FS}}$	Forward Transconductance	$V_{DS}=-5\text{V}$ , $I_D=-20\text{A}$	110			S
$V_{\text{SD}}$	Diode Forward Voltage	$I_S=-1\text{A}$ , $V_{GS}=0\text{V}$		-0.5	-1	V
$I_S$	Maximum Body-Diode Continuous Current <sup>G</sup>				-50	A
<b>DYNAMIC PARAMETERS</b>						
$C_{\text{iss}}$	Input Capacitance	$V_{GS}=0\text{V}$ , $V_{DS}=-10\text{V}$ , $f=1\text{MHz}$		5626		pF
$C_{\text{oss}}$	Output Capacitance			928		pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			716		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}$ , $V_{DS}=0\text{V}$ , $f=1\text{MHz}$		3	6	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g$	Total Gate Charge	$V_{GS}=-4.5\text{V}$ , $V_{DS}=-10\text{V}$ , $I_D=-20\text{A}$		70	100	nC
$Q_{\text{gs}}$	Gate Source Charge			9.2		nC
$Q_{\text{gd}}$	Gate Drain Charge			18.4		nC
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{GS}=-4.5\text{V}$ , $V_{DS}=-10\text{V}$ , $R_L=0.5\Omega$ , $R_{\text{GEN}}=3\Omega$		18		ns
$t_r$	Turn-On Rise Time			52		ns
$t_{\text{D(off)}}$	Turn-Off Delay Time			285		ns
$t_f$	Turn-Off Fall Time			123		ns
$t_{\text{rr}}$	Body Diode Reverse Recovery Time	$I_F=-20\text{A}$ , $dI/dt=500\text{A}/\mu\text{s}$		78		ns
$Q_{\text{rr}}$	Body Diode Reverse Recovery Charge	$I_F=-20\text{A}$ , $dI/dt=500\text{A}/\mu\text{s}$		495		nC

A. The value of  $R_{\text{QJA}}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The Power dissipation  $P_{\text{DSM}}$  is based on  $R_{\text{QJA}}$ ,  $t \leq 10\text{s}$  value and the maximum allowed junction temperature of  $150^\circ\text{C}$ . The value in any given application depends on the user's specific board design.

B. The power dissipation  $P_D$  is based on  $T_{J(\text{MAX})}=150^\circ\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature  $T_{J(\text{MAX})}=150^\circ\text{C}$ . Ratings are based on low frequency and duty cycles to keep initial  $T_J=25^\circ\text{C}$ .

D. The  $R_{\text{QJA}}$  is the sum of the thermal impedance from junction to case  $R_{\text{QJC}}$  and case to ambient.







E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.






F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of  $T_{J(\text{MAX})}=150^\circ\text{C}$ . The SOA curve provides a single pulse rating.

G. The maximum current rating is package limited.

H. These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ .

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**



**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**


Figure 12: Single Pulse Avalanche capability (Note C)




Figure 13: Power De-rating (Note F)




Figure 14: Current De-rating (Note F)




Figure 15: Single Pulse Power Rating Junction-to-Ambient (Note H)












Figure 16: Normalized Maximum Transient Thermal Impedance (Note H)

**Gate Charge Test Circuit & Waveform**

**Resistive Switching Test Circuit & Waveforms**

**Unclamped Inductive Switching (UIS) Test Circuit & Waveforms**

**Diode Recovery Test Circuit & Waveforms**


# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by Alpha & Omega manufacturer:***

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)  
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)  
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)  
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)  
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)  
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)