



Data Sheet

Type Number: 5622

System: Nickel Metal Hydride/

KOH Electrolyte

Nominal Voltage [V]: 8.4

Nominal Capacity C [mAh]: 140

Typical Capacity C [mAh]: 150

at 28 mA / 7.00 V

Weight, approx. [g] 47

 Dimensions [mm]:
 min.
 max.

 Length [l]:
 47.5
 48.5

 Width Facing [w]:
 25.5
 26.6

 Height [h]:
 15.0
 15.7

UL Recognition: MH 13654 (N)

Coding: TBA

Temperature Ranges [°C] min. max.

 Storage: less than 30 days
 -40
 65

 Discharge:
 -20
 65

 Charge:
 0
 65

Charging Method:

Normal Charging: 14 mA for 14 - 16 h Accelerated Charging (20°C): 28 mA for 7-8 h Fast Charging: 70 mA for 3 h *

Time controlled, voltage control recommended

Trickle Charging: 4.2 mA

Overcharge (20°C): 14 mA continuous

28 mA up to 1 year

Charge Retention [%] at 20°C: 90

Capacity available after 1 month Storage at 20°C

Internal Resistance [Ohm]: 5.6

at charged cells, 20°C, DC: 0.2 CA/2 CA, (IEC 61951-2)

Impedance [Ohm]: 0.9

at charged cells, 20°C, AC: 1kHz, (IEC 61951-2)

Typical Capacities [mAh]:

at 140 mA / 6.3 V 88

Max. Discharge Current (cont.) [mA]: 280

Life Expectancy (typical):

IEC Cycle: 1000 Cycles

Trickle Charge: up to 6 years (20°C)

Trickle Charge: up to 3 years (45°C)

Capacities based on normal charging



Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

 $^{^{\}ast}\,$ for fully discharged cells, 20 $^{\circ}\text{C}\,$

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for varta manufacturer:

Other Similar products are found below:

56456 702 099 18750 4114 210 501 4610 726 406 4122 210 511 LCD-CHARGER + 4XAA 2400MAH 449915B 4607 726 406
55171403014 55625603059 55615602940 4112101411 4 022 211 111 4 106 101 436 4 020 211 111 MINI CHARGER + 2XAA 2100MAH
MINI-CHARGER 17730 LCD-SMART-CHARGER 414086X POCKET-CHARGER + 4XAA 2100MAH 458980A LCD MULTI
CHARGER CG511-150-PB EE UNIVERSAL CHARGER CG401D-050-PB CG511-050-PB CU303-018-PB 413675G CG381D-G-100-PB
CU202-030-PB 55615603059 CG381D-G-150-PB CG481G-050-PB CU303-030-PB CG511D-030-PB CA317-PB CU201G-B-030-PB
095668F 4600 726 406 CA418-PB CG481G-030-PB CG511D-100-PB CG511-030-PB CG381D-G-050-PB CU302-030-PB CG341-030-PB CU201G-B-050-PB CA39-PB