



Outdoor Masking Poly Tape

5903

Technical Data

October, 2008

Product Description

3M™ Outdoor Masking Poly Tape 5903 is designed for construction, remodeling and maintenance jobs. It is made with heavy duty polyethylene film and synthetic rubber adhesive. It is UV weather resistant and removes cleanly for up to one month with little or no adhesive residue on most opaque surfaces without deteriorating.

Product Construction

Backing	Adhesive	Color	Standard Roll Length	Standard Roll Width
Polyethylene	Synthetic Rubber	Red	60 yds. (54.8 m)	1.88 in. (48 mm)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	79 oz./in. width (87 N/100 mm)	D-3330
Tensile Strength:	21 lbs./in. width (368 N/100 mm)	D-3759
Elongation at Break:	72%	D-3759
Thickness:	7.5 mils (0.19 mm)	D-3652
Temperature Use Range:	Up to 173°F (78°C)	

Features

- Clean removal from most opaque surfaces up to 30 days.
- UV resistant backing.
- Aggressive rubber adhesive grabs and adheres well to many surfaces.
- Hand tearable.
- Conformable backing.
- Red color for good visibility. Color insures that the tape is not accidentally left on.
- Excellent choice for outdoor holding and window and door masking jobs.

Application Ideas

- Ideal for overspray protection when masking substrates from coatings such as stucco, EIFS, gel coat, and construction coatings.
- Ideal for holding, bundling and securing.
- Can be used on surfaces such as window and door frames to protect them from damage during construction.
- Adhesive layer holds well to irregular surfaces such as sealed masonry or brick.
- Excellent for temporary repairs on the job.

3M™ Outdoor Masking Poly Tape

5903

Storage Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% RH in the original carton.

Shelf Life To obtain best performance, use this product within 18 months from date of manufacture.

Technical Information The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Warranty, Limited Remedy, and Disclaimer Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2008 70-0711-0202-7 (10/08)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [3m manufacturer](#):

Other Similar products are found below :

[SC401U](#) [98-0003-3071-6](#) [80-0012-6467-2](#) [00-054007-70220-7](#) [00-054007-34717-0](#) [5952-3/4"x15yds](#) [6840-2X50-GRAY](#) [6A11-A0121-007.0-0](#) [701-W](#) [7993MP-2CIRCLE-100](#) [FE-5100-5126-4](#) [FE-5100-5273-4](#) [FE-5100-5492-0](#) [8124/14](#) [812510-100](#) [8125/17](#) [813216](#) [8204-3LFM](#) [8425-8](#) [MNG14BCX](#) [FP301-1-6"-Clear](#) [FV14-6C](#) [920102-01-25-R](#) [927739-40](#) [929835-01-28-RK](#) [951240-2520-AR-PR](#) [960X/980X](#) [98-0003-3075-7](#) [HF365/16SF](#) [HF36564-100](#) [HF625/26-30](#) [1/2-5-4492W](#) [1/2-5-5430](#) [1/2-5-850S](#) [1/2-5-3431](#) [12X12-6-4056B](#) [12X12-6-433](#) [12X12-6-4930](#) [1311](#) [13-500-NB](#) [14526-EZ5B-300-02C](#) [1-4-4658F](#) [14520-EZAB-300-0EC](#) [14T26-SZLB-200-0LC](#) [14T50-SZWB-100-0NC](#) [1-5-3437](#) [1-5-4496W](#) [1-5-4943F](#) [1-5-363](#) [1-5-5451](#)