

datasheet for MLS WG 100/2,5  
 article number: 934083100



product description:	
<b>description:</b>	order number: 934 083-100
<b>description:</b>	Safety measuring lead, at either end 4 mm diameter safety connector with straight/rectangular outlet and integrated kink protection. Nickel-plated copper beryllium contact spring. Highly flexible, double insulated stranded lead, shatter-proof grip sleeve and lead. Color indicator for the recognition of damage to the insulation. In accordance to IEC 61010 standard.
<b>typ:</b>	MLS WG 100/2.5 schwarz / black
<b>system:</b>	4mm safety system
<b>order number:</b>	934 083-100
<b>color</b>	●
<b>other color versions:</b>	●●●●●●
technical data	
<b>measurement category acc. to IEC 61010:</b>	CAT III
<b>pin dimensions</b>	4 mm
<b>type of contact:</b>	pin (spring loaded)
<b>cable type:</b>	LEH-XY
<b>cable specification:</b>	highly flexible lead
<b>wire stranding:</b>	320 x 0.10 mm
<b>rated voltage:</b>	AC/DC 1000 V
<b>rated current:</b>	32 A
<a href="#">Please consider derating curve!</a>	
<b>contact resistance:</b>	12 mOhm
<b>cable length:</b>	100 cm
<b>conductor size:</b>	2.5 mm <sup>2</sup>
<b>cable material:</b>	PVC
<b>cable color:</b>	black
material	
<b>contact material:</b>	contact spring: copper - beryllium
<b>contact surface material:</b>	nickel
<b>housing material:</b>	PA
environmental conditions:	
<b>temperature range:</b>	-15 °C to +70 °C

<b>inflammable class:</b>	
<b>housing (basic material):</b>	UL 94 V - 2
<b>drawing</b>	
	<p>Technical drawing of a component with the following dimensions:</p> <ul style="list-style-type: none"> <li>Top diameter: <math>\varnothing 7,8</math></li> <li>Inner diameter: <math>\varnothing 4</math></li> <li>Vertical length: 46,3</li> <li>Horizontal length: 54,3</li> <li>Bottom diameter: <math>\varnothing 4</math></li> <li>Bottom diameter: <math>\varnothing 7,8</math></li> </ul>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Test Leads](#) category:*

*Click to view products by [Hirschmann](#) manufacturer:*

Other Similar products are found below :

[R928010000](#) [R928142000](#) [15101](#) [15107](#) [15115](#) [15117](#) [15301](#) [15303](#) [15304](#) [15102](#) [15120](#) [15308](#) [15302](#) [15306](#) [15307](#) [15502](#) [15403](#) [15407](#)  
[15409](#) [15501](#) [15506](#) [EM3782-12-7#](#) [EM4702-12-0](#) [BU-1149-A-36-0](#) [BU-1481-E-12-0](#) [BU-1481-E-24-0](#) [2524-A-60](#) [924961-C](#) [924964-C](#)  
[924966-C](#) [924967-C](#) [LB1F-2R-RED](#) [LB1F-2R-YLW](#) [2500](#) [2501](#) [2524-A-48](#) [2977-J-48](#) [R928051000](#) [R928141000](#) [R928143000](#)  
[R948131000](#) [BU-1449-E-12-2](#) [BU-1480-E-24-0](#) [BU-1481-E-12-2](#) [BU-1481-E-24-2](#) [LB1F-2R-BLK](#) [LB1F-2R-BLUE](#) [EM3782-12-8#](#)  
[EM4702-18-2](#) [6345](#)