


TECHNICAL DATA SHEET	code	MRG5801
	version	1
	date	2006-03-29
	page	1/2

APPLICATION

Coaxial communication cable based on MIL-C-17.

CONSTRUCTION




- | | | |
|---|-----------------|--|
| 1 | Inner conductor | Stranded tinned copper |
| 2 | Dielectric | Solid PE |
| 3 | Braid | Annealed tinned copper |
| 4 | Sheath | LSNH according the European Standard HD 624. |

REQUIREMENTS AND TEST METHODS

Test methods in accordance with European standard EN 50289.

Mechanical characteristics

1. Inner conductor:
 - Diameter: 19 x 0.18 mm ± 0.02 mm
2. Dielectric:
 - Diameter: 2.95 mm ± 0.15 mm
3. Outer conductor:
 - Diameter screen: 3.5 mm ± 0.2 mm
 - Coverage braid: 93 % ± 4 %
4. Sheath:
 - Diameter: 4.95 mm ± 0.2 mm
 - Tensile strength: ≥ 9.0 N/mm²
 - Elongation at break: ≥ 125 %
5. Cable:
 - Crush resistance of cable: < 1% (load of 700N)
 - Temperature range -storage/operating: -15°C to +70°C
 - Temperature range -installation: -5 °C to + 50°C
 - Minimum static bend radius: 25 mm
 - Total weight: 38 kg/km

	TECHNICAL DATA SHEET	code	MRG5801
		version	1
	Coax cable	date	2006-03-29
	RG58 C/U LSF	page	2/2

Electrical characteristics

Mean characteristic impedance:	$50 \pm 2 \Omega$
Regularity of impedance:	> 40 dB
DC resistance inner conductor:	$\leq 36 \Omega/\text{km}$
Capacitance:	$100 \text{ pF/m} \pm 2 \text{ pF/m}$
Nominal velocity of propagation:	66 %
Insulation resistance:	$> 10^4 \text{ M}\Omega.\text{km}$
Voltage Rating	
DC:	4 kVdc
RMS	2kVrms

Return loss at	5-30 MHz:	$\geq 20 \text{ dB}^*$
	30-470 MHz:	$\geq 20 \text{ dB}^*$
	470-1000 MHz:	$\geq 18 \text{ dB}^*$

*Max. 3 peak values 4 dB lower than specified.

Nominal Attenuation:

10 MHz:	4.5 dB/100m
200 MHz:	22.0 dB/100m
400 MHz:	32.0 dB/100m
1000 MHz:	50.0 dB/100m
2400 MHz:	79.0 dB/100m
3000 MHz:	88.0 dB/100m



Belden CDT believes this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [belden](#) manufacturer:

Other Similar products are found below :

[HIPWP2LA](#) [8916-BRN-100](#) [8916-GRN/YEL-500](#) [8916-YEL-500](#) [8918-GRY-1000](#) [8919-DK-BLU-100](#) [5T00UP 008500](#) [7810A-BLK-500](#)
[7860NBH](#) [7934A-BLK-1000](#) [7937A-BLK-1000](#) [8019-100](#) [8058](#) [8080](#) [8108-060-1000](#) [8125-CHR-100](#) [8132-CHR-1000](#) [8133-CHR-1000](#)
[8155-CHR-1000](#) [8162-060-1000](#) [8162-CHR-1000](#) [8164-CHR-100](#) [8164-CHR-1000](#) [8185-CHR-100](#) [8205-CHR-1000](#) [8221-BLK-1000](#) [8233-](#)
[010-1000](#) [8233-BLK-1000](#) [8237-BLK-500](#) [8238-BLK-500](#) [8241A-BLK-1000](#) [8241F-RED-MATTE-1000](#) [8263-BLK-U1000](#) [8279-BLK-](#)
[1000](#) [8281-003-1000](#) [8281 010500](#) [83002 0101000](#) [83003-006-500](#) [83007 0081000](#) [83008 0091000](#) [83010-RED-100](#) [83029 0021000](#) [8302-](#)
[CHR-500](#) [8303 060500](#) [8307-CHR-100](#) [8310-060-1000](#) [8310-CHR-1000](#) [83305E 009100](#) [83347E 009100](#) [8348-060-500](#)