

This document was generated on 02/24/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:	19003-0020 Active Standard Quick-Disconnect InsulKrimp [™] Quick Disconne 4.75 x 0.81mm	<u>Terminals</u> ect, Female, for 18-22 (0.80-0.35mm²), Mylar Tape, Tab	E CONTRACTOR OF
Documents: <u>3D Model</u> <u>Drawing (PDF)</u> Product Specification	<u>PS-19902-008 (PDF)</u>	Product Specification PS-19902-011 (PDF) Product Specification PS-19902-015 (PDF) RoHS Certificate of Compliance (PDF)	MOLDED NYLON INSULATED HOUSING Series image - Reference only
Agency Certifica CSA UL General Product Family Series Comments Crimp Quality Equipm Insulated Overview Product Name Type UPC Physical Barrel Type Color - Resin Flammability Gender Glow-Wire Compliant Insulation Lock to Mating Part Material - Plating Mat Material - Plating Term Material - Resin Net Weight Orientation Packaging Type Plating min - Mating Plating min - Termina	ing mination	LR18689 E79133 Quick Disconnects <u>19003</u> Funnel Entry Yes Fully Standard Quick-Disconnect Terminals InsulKrimp [™] Quick Disconnect 800753028708 Closed Red 94V-2 Female Yes Nylon (PA) None Brass Tin Tin Nylon 0.685/g Straight Adhesive Tape on Reel 4.064µm 4.064µm	EU RoHS China RoHS Compliant REACH SVHC Not Reviewed Image: Compliant Status Low-Halogen Status Image: Compliant Status Need more information on product environmental compliance? Search Parts in this Section for any non-product compliance questions. Please visit the Contact Us section for any non-product compliance questions. Search Parts in this Series 19003 Series Application Tooling FAQ Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document. Global Product # Description Product # Mini-Mac TM 0638857000
Polarized to Mating P Tab Thickness Tab Width Temperature Range Termination Interface Wire Insulation Diame Wire Size AWG Wire Size mm ² Electrical Voltage - Maximum	Operating : Style	No 0.81mm 4.75mm -65°C to +105°C Crimp or Compression 3.43mm max. 18, 20, 22 0.35 - 0.80 600V	Applicator ATP Crimp Dies <u>0192880049</u> for the Tape Crimp Module and ATP-101 & 301 Press

Material Info Old Part Number PS-19902-008, PS-19902-011, PS-19902-015 SD-19003-005

This document was generated on 02/24/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Terminals category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

HT-13-10 71M-250-32-NB 01-2065-1-0216 00581P0075 M10-10RX M10BCK 60205-1 604200-1 60598-1-CUT-TAPE 60617-1-C 60873-1 M14-516R/SK M14-6RSX M18-10FLX M18-8FBX M18-8R/LX M18BCK 61314-6-C 61-S 61-SN-A 62149-1 62-NBM-A 63-S 640179-1 640917-2-CUT-TAPE 6501550002 66107-2-C 66107-4-C 696683-1 696834-1 696861-1 696931-1 696999-1 M8-516RK M86700006 MA250DMFMX-A 701-2007 701-2307 701-7761-03 70F-110-32-PB 718-N-A 71M-187-20-NBL 71M-250-32-NBL 72F-187-20-NBL 72M-250-32-NBL 7310 73F-250-32 73F-250-32-NBL 73F-250-32-NL F-1M