Standard **□** 1/2" range

SX.LA 1/2" drive long-reach Torx® bit sockets

• Non-removable bits.

= 0	Torx® no.	⊥≭ A mm	D mm	l mm	L mm	∆∏∆ g
SX.40LA	T40	6,60	22,8	84	120	95
SX.45LA	T45	7,77	22,8	84	120	95
SX.55LA	T55	11,17	22,8	104	140	220
SX.70LA	T70	15,49	23,1	104	140	280



Set of 1/2" drive Torx® bit sockets

AMEX.3

• Comprising: SXM.20, SXM.25, SXM.27, SXM.30, SXM.40, SXM.45, SXM.50, SXM.55, SXM.60.

• Plastic case BP.102 : 204 x 122 x 52 mm.

• Tray PL.455. Δ\(\text{\Delta}\) : 865 g.




SV.B 1/2" drive XZN® spline bit sockets

• Non-removable bits.

=	Ø Screw	D mm	l mm	L mm	∆T∆ g
SV.6B	M6	22,8	24	60	60
SV.8B	M8	22,8	24	60	60
SV.10B	M10	22,8	24	60	70
SV.12B	M12	22,8	24	60	80
SV.14B	M14	22,8	24	60	100
SV.16B	M16	23,1	24	60	110






SV.LB 1/2" drive long-reach XZN® spline bit sockets

Non-removable bits.

= 0	Ø	D	- 1	L	$\Delta \Delta$
	Screw	mm	mm	mm	g
SV.6LB	M6	22,8	64	100	80
SV.8LB	M8	22,8	64	100	80
SV.10LB	M10	22,8	64	100	90
SV.10ELB	M10	22,8	120	120	110
SV.12LB	M12	22,8	64	100	120
SV.12ELB	M12	22,8	104	140	150
SV.14LB	M14	22,8	64	100	150







Special \square 1/2" sockets for automotive applications

For details of our 1/2" special automotive sockets, see section 18.

- Spark plug sockets
- Cylinder head sockets
- Injector sockets



Rack sets of 1/2" drive bit sockets

ST: for hexagon socket heads.

SX: for Torx® heads.

SV: for XZN® spline heads.

3 0	Sizes	Rack	ΔŪΔ g
ST.40	STM 6-8-10-12-14-17-19	CKS.97	830
ST.41	SHPLA 6-7-8-10-12	CKS.90	610
SX.41	SXM 20 - 25 - 27 - 30 - 40 - 45 - 50 - 55	CKS.95	640
SV.40A	SVA 6-8-10-12	CKS.90	340
SV.41A	SVLB 8-10-12	CKS.90	440







X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for facom manufacturer:

Other Similar products are found below:

92A.5,5 ARB.5.5X40 AMR ANXR10X75 AEF.J6 AEF.J1 EH.107 EH.103 256.2.5 MT.J3 986058 75.10 84E.J1 455B 440.19 44.6X7 440.6 440.21 R.306-25D R.217 R.5 J.13LA 431.LE 405.10 425.E 405.12E R.216 601 AEF.1,5X35 AEFP.00X35 AEX.J2 AEX.9X75 AEX.7X35 251A.2.5 HB.2B 440.20 435.E 432.LMT 44.12X13 440.5H 440.22 R.304DA 427.MT 416.PMT 113A.6C 113A.10C 251A.3 89S.JP8 AEF.1,8X35 75.7