

This document was generated on 04/06/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	19005-0014		
Status:	Active		▶.
Overview: Standard Quick-Disconnect		t Terminals	FUNNEL
Description:	InsulKrimp™ Fully Insulated Female Quick Disconnect, for 10-12 AWG Wire,		
	Continuous Molded Strip		
			E C C C C C C C C C C C C C C C C C C C
Documents:			CC STOP
<u>3D Model</u>		Product Specification PS-19902-011 (PDF)	MOLDED NYLON INSULATED HOUSING
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
Product Specification	PS-19902-008 (PDF)		_ image - Reference only
Agency Certifica	tion		
CSA		LR18689	EU RoHS China RoHS
UL		E79133	ELV and RoHS
			Compliant
General			REACH SVHC
Product Family		Quick Disconnects	Not Reviewed
Series		<u>19005</u>	Low-Halogen Status
Crimp Quality Equipn	nent	Yes	Low-Halogen
Insulated		Fully	Need more information on product
Overview		Standard Quick-Disconnect Terminals	environmental compliance?
Product Name		InsulKrimp™	
Туре		Quick Disconnect	Email productcompliance@molex.com
UPC		800753030633	For a multiple part number RoHS Certificate of
Physical			Compliance, <u>click here</u>
Physical Demol Trans		Classed	Please visit the Contact Us section for any
Barrel Type		Closed Yellow	non-product compliance questions.
Color - Resin		94V-2	
Flammability		94v-2 Female	
Gender Glow-Wire Compliant		Yes	
Insulation		Nylon (PA)	Connak Danta in this Conice
Lock to Mating Part		None	Search Parts in this Series
Material - Metal		Brass	<u>19005</u> Series
Material - Plating Mat	ing	Tin	
Material - Plating Ter		Tin	Use With
Material - Resin	mination	Nylon	<u>19004-0009</u> , <u>19004-0012</u>
Net Weight		1.459/g	
Orientation		Straight	Application Tooling FAQ
Packaging Type		Reel	Tooling specifications and manuals are
Polarized to Mating P	art	No	found by selecting the products below.
Tab Thickness		0.81mm	Crimp Height Specifications are then
Tab Width		6.35mm	contained in the Application Tooling
Temperature Range -	Operating	-65°C to +105°C	Specification document.
Wire Insulation Diame		6.99mm max.	Global
Wire Size AWG		10, 12	Description Product #
Wire Size mm ²		3.30 - 5.00	Mini-Mac™ <u>0638830300</u>
			Applicator
Electrical			ACP Perishable <u>0190280051</u>
Voltage - Maximum		600V	Tool Kit used in ACP
			presses that process
Material Info			continuous molded
Old Part Number		C-2265C	product
Reference - Drav	-		
Product Specification		PS-19902-008, PS-19902-011	
Sales Drawing		SD-19005-001	

This document was generated on 04/06/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Terminals category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

HT-13-10 71M-250-32-NB 01-2065-1-0216 00581P0075 M10-10RX M10BCK 60205-1 604200-1 60598-1-CUT-TAPE 60617-1-C 60873-1 M14-516R/SK M14-6RSX M18-10FLX M18-8FBX M18-8R/LX M18BCK 61314-6-C 61-S 61-SN-A 62149-1 62-NBM-A 63-S 640179-1 640917-2-CUT-TAPE 6501550002 66107-2-C 66107-4-C 696683-1 696834-1 696861-1 696931-1 696999-1 M8-516RK M86700006 MA250DMFMX-A 701-2007 701-2307 701-7761-03 70F-110-32-PB 718-N-A 71M-187-20-NBL 71M-250-32-NBL 72F-187-20-NBL 72M-250-32-NBL 7310 73F-250-32 73F-250-32-NBL 73F-250-32-NL F-1M