


APH-071-10-08-S


Peltier cooler module

Data sheet



- Input (Black)

+ Input (Red)



I_{max}	[A]	6.0
V_{max}	[Vdc]	8.6
$P_{c\ max}$	[W]	23
ΔT_{max}	[°C]	65
A	[mm]	20
A1	[mm]	20
B	[mm]	20
H	[mm]	2.8
L	[mm]	100
Wire	AWG	n/a

(At hot side temperature $Th = 25^\circ C / 298K$, under dry N_2).

$P_{c\ max}$ = Cooling power at $\Delta T = 0$ and $I = I_{max}$.

ΔT_{max} = Temperature difference at $I = I_{max}$ and $P_c = 0$.

Max hot side temperature $Th = 80^\circ C$ for best long term performance.

Max mounting pressure: 1.5MPa.


Wires: UL-style 1569, 105oC (Unstripped).



APH-071-10-08-S

Peltier cooler module


Data sheet - At hot side temperature 25°C



APH-071-10-08-S

Peltier cooler module


Data sheet - At hot side temperature 50°C



APH-071-10-08-S

Peltier cooler module

Data sheet - At hot side temperature 75°C



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for european thermodynamics manufacturer:

Other Similar products are found below :

[AP3-070-20-25](#) [APHC-12706-S](#) [SF-06-150-S](#) [APH-031-10-13-S](#)