


APHC-03I03-S

Peltier cooler module

Data sheet



I _{max}	[A]	2.5
V _{max}	[Vdc]	3.6
P _c max	[W]	6
ACR	[Ω]	1.2
ΔT _{max}	[°C]	65
A	[mm]	16
A _l	[mm]	16
B	[mm]	20.5
H	[mm]	3.94
L	[mm]	100
Wire	AWG	20

- (At hot side temperature $T_h = 27^\circ\text{C} / 300\text{K}$, under dry N_2)
- P_c max = Cooling power at $\Delta T = 0$ and $I = I_{max}$
- ΔT_{max} = Temperature difference at $I = I_{max}$ and $P_c = 0$
- Max hot side temperature $T_h = 200^\circ\text{C}$ for best long term performance
- Max mounting pressure: 1.5MPa
- Wires: UL-style 1569, 105°C (Unstripped)

Features


- RoHS and Reach 161 compliant
- Solid-state reliability
- Built with high temperature solder with the ability to withstand $<200^\circ\text{C}$ assembly processing temperatures for short periods of time
- High integrity nickel diffusion barriers on elements
- High strength for rugged environments
- Porched style for enhanced leadwire strength
- Sealed & lapped for multi-module applications



APHC-03I03-S

Peltier cooler module


Data sheet - At hot side temperature 25°C



APHC-03I03-S

Peltier cooler module


Data sheet - At hot side temperature 50°C



APHC-03I03-S

Peltier cooler module

Data sheet - At hot side temperature 75°C



C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for european thermodynamics manufacturer:

Other Similar products are found below :

[AP3-070-20-25](#) [APHC-12706-S](#) [SF-06-150-S](#) [APH-031-10-13-S](#)