



Government Solutions

Market

- Defense
- Energy
- Green Solutions
- Health Safety
- Homeland Security

Contracts

- General Services Administration
- Veterans Affairs

Product Information

- Government Catalogs
- Online Product Catalog
- FEDSPEC Locator
- NSN Locator
- Product Catalog

News

- Industry Links

Contact Information

- Contact Us

Product Catalog for Government Solutions > Defense Solutions > Aircraft Maintenance Products > 3M™ Electrical Products > 3M™ Heat Shrink Tubing > 3M™ Single Wall Polyolefin Tubing > 3M™ FP-VW Tubing > 3M™ FP-301 VW Tubing, 3/8 inch > 3M™ FP-301 VW Tubing, 3/8 inch, Black >

## 3M™ Heat Shrink FP-301VW-3/8-Black-200', 200 ft Length per spool, 3 spools per case



[Click to Enlarge](#)

3M™ Tubing FP-301VW has the same outstanding balance of electrical, physical and chemical properties as FP-301 tubing and is specially engineered for superior flame resistance. This tubing comes in a spool.

Where To Buy

[Where to Buy](#)

Quick Links

- [Contact Us](#)
- [Material Safety Data Sheets \(MSDS\)](#)
- [OH&ES Distributor Login](#)
- [Industrial Distributor Login](#)

Additional Information

3M™ Tubing FP-301VW is rated for continuous operation from -55°C (-67°F) to 135°C (275°F) and withstands elevated temperatures to 300°C (572°F) for brief periods. Minimum shrink temperature for all FP-301VW tubing is 100°C (212°F).

**3M ID:** 80-6102-1960-4

**GTIN(UPC/EAN):** 0 00 54007 08492 1

Characteristics:

Name	Value
Agency Approvals	UL Recognized and CSA Certified
China RoHS - Below MCV	Yes
Color	Black
Dielectric Strength	900 Volt
Elongation	400 Percent
EU RoHS Compliant	Yes
Expanded Inner Diameter	3/8 Inch
Flammability Rating	UL 224 VW-1 / CSA 0ft
Length	200 Linear Foot
Material	Highly Flame-Retardant, Flexible Polyolefin
Mil Spec	AMS-DTL-23053/5, Class 3
Non-Corrosive	Yes
Operating Temperature Range (Celsius)	-55 Degrees C to +135 Degrees C
Recovered Inner Diameter	3/16 Inch
Shrink Ratio	2:1
Tensile Strength	2400 Pound-Force Per Square Inch
Tubing Type	Single-Wall Polyolefin Flexible-Highly Flame Retardant
UL File Number	E-39100



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:*

*Click to view products by [3M](#) manufacturer:*

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR8248-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [617867N001](#) [6500750004](#) [D-306-38](#) [770-003S106W2](#) [770-005S105W1](#) [770-005S106W1](#) [770-007A303](#) [770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [790-3012](#) [MFT-MT2000-NO.14-0-SP](#) [MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#) [MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-1-6"-Clear](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#) [121-018-40](#) [121-123-1-1-32BTC](#)