

3M™ Chemicals for Electronics Markets

Products

- Aerosol Cleaners
- Battery Materials
- Electronic Liquids
- Electronic Coatings
- Electronic Surfactants
- Engineered Fluids
- 1230 Fire Protection Fluid
- Organic Electronics
- Performance Fluids
- Specialty Gases

Solutions

- Aerospace
- Archives & Museums Fire Protection
- Automotive & Transportation
- Data Processing & Control Rooms
- Electronics
- Fire Protection
- Hard Disk Drive
- Marine
- Medical Devices
- Military
- Museum & Preservation
- Oil & Gas
- Precision Optics
- Semiconductor
- Telecommunications

Resources

- Contact Us
- MSDS
- 3M RoHS/REACH Declaration
- Tech Support
- Technical Documents and Literature
- Where to Buy

Product Catalog for > Electrical Products . . . 3M™ Tubing FP-301, 3/16 inch > 3M™ Tubing FP-301, 3/16 inch, Black >

3M™ Heat Shrink Thin-Wall Tubing FP-301-3/16-Black-250' : 250 ft spool length, 750 linear ft/box

[Printer-friendly format](#)

3M™ Heat Shrink Tubing FP-301 offers an outstanding balance of electrical, physical and chemical properties for a wide variety of industrial and military applications. This tubing comes in a bulk spool.

3M Id : 80-6102-1946-3
 : FP-301-3/16-Black-250'*
 GTIN(UPC/EAN) : 0 00 54007 08478 5

Additional Information

3M™ Thin Wall Tubing FP-301 is a heat shrinkable flexible polyolefin tubing that offers an outstanding balance of electrical, physical and chemical properties for a wide variety of industrial and military applications. Rated for 275°F (135°C) continuous operation. FP-301 tubing is typically used as a shrink-fit electrical insulation over cable splices and terminations. It is also used for lightweight wire harness covering, wire marking, wire bundling, component packaging and fire resistant covering. FP-301 clear tubing provides excellent visibility for component packing. All FP-301 tubing is split resistant, mechanically tough, easily marked and resists cold flow. FP-301 is available in black, white, red, blue, yellow and clear in the standard lengths of 6-inch (15,2 cm) cut pieces, 48-inch (1,21 m) and small (8.5-inch core diameter) spools of 50 (15,24 m) and 100 (30,48 m) feet. Four-foot lengths of green tubing are available in sizes 1/16 inch to 1/2 inch. The Assorted Color Kit

[Full Text . . .](#)

Characteristics

Agency Approvals	UL Recognized, CSA Certified, ABS, and AMS 3636 & 3637
China RoHS - Below MCV	Undetermined
Color	Black
Dielectric Strength	900 Volt
Elongation	400 Percent
EU RoHS Compliant	Undetermined
Expanded Inner Diameter	3/16 Inch
Flammability Rating	UL 224 All Tubing Flame Test
Length	250 Linear Foot
Material	Flexible Polyolefin
Mil Spec	AMS-DTL-23053/5, Class 1
Non-Corrosive	Yes
Operating Temperature Range (Celsius)	-55 Degrees C to +135 Degrees C
Recovered Inner Diameter	3/32 Inch
Shrink Ratio	2:1
Tensile Strength	2400 Pound-Force Per Square Inch
Tubing Type	Single-Wall Polyolefin Flexible
UL File Number	E-39100

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [3M](#) manufacturer:

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR8248-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [617867N001](#) [6500750004](#) [D-306-38](#) [770-003S106W2](#) [770-005S105W1](#) [770-005S106W1](#) [770-007A303](#) [770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [790-3012](#) [MFT-MT2000-NO.14-0-SP](#) [MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#) [MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-1-6"-Clear](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#) [121-018-40](#) [121-123-1-1-32BTC](#)