



Desoldering Tools & Accessories.

PT209

Micro-Tipped SOLDAPULLT III with MRT16 Tip and OSB32 O-Ring

Specification:

L: 12.0 in. (304.0 mm)



US340

Static-Safe Universal SOLDAPULLT with LS197 Tip and ODS31 O-Ring L: 8.0 in. (203.0 mm)



SS350

Static-Safe Standard Metric SOLDAPULLT Challenger with LS363 Tip and OS130 O-Ring Our only tool with a metal barrel



DS017

Deluxe SOLDAPULLT with SRT12 Tip and ODS31 O-Ring



Specification:

L: 13.0 in. (330.0 mm)

LS197

Static-Safe Replacement Tip for AS196, DS017LS, US340 and PT409

Specification:

ID: .125 in. (3.2 mm) L: .536 in. (13.6 mm)



SRT12

Standard Replacement Tip for DS017, PT109 and US140

Specification:

ID: .125 in. (3.2 mm) L: .536 in. (13.6 mm)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [edsyn manufacturer](#):

Other Similar products are found below :

[LN 261](#) [LN270](#) [SW021/2,0/30](#) [PUK 10 ALL](#) [SLT01](#) [ST706](#) [MA10LS](#) [MA 1070](#) [OS130](#) [SU8500-S5](#) [SS 350 G CHALLENGER](#) [AN122](#)
[FXM5002](#) [SR670](#) [ZD12](#) [FXS5008](#) [ET110](#) [MA10](#) [SAC5250](#) [CB138](#) [SP 375 B](#) [LS363](#) [OL111](#) [AS196](#) [CS468-1](#) [HS307](#) [LT382LF](#) [FL911](#)
[SAC1250-3](#) [SA8250](#) [WL675](#) [FL 19 222](#) [SS8500](#) [SP 625 B](#) [RB641](#) [HS106BC](#) [HS106BC-5](#) [SA1250](#) [PT109](#) [SAC5250-3](#) [SC8250](#) [SP 250 B](#)
[SP 500](#) [LP 20 PIXTER](#) [SC1250](#) [LN 260 B](#) [LT392LF](#) [LT394](#) [SW2.5/15](#) [ALM 2010](#)