

**Tripp Lite** Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

## Universal Reversible USB 2.0 Cable (Reversible A to 5Pin Micro B M/M), 6-in.

### MODEL NUMBER: UR050-06N



### **Highlights**

- Next Generation USB Digital **Device Connector**
- Provides both Data and Power transfers
- USB 2.0 480Mbps Transfer rates
- Universal / Reversible "A" Male to Micro-B Male

#### System Requirements

• Digital devices that use the USB Micro-B Female socket

#### **Package Includes**

• 6-in. USB2.0 Universal / Reversible A to Micro-USB B Device Cable (A Male to Micro-B Male)

#### Description

Tripp Lite UR050-06N, 6-in. USB 2.0 A to Micro-B cable, features a Universal / Reversible "A" connector, which takes the guesswork out of which way to position the "A" connector for plugging. Micro-USB is the next generation of USB connector that will be found on Cell Phones, PDA's, USB On-the-Go (OTG) devices, Digital Cameras, and more. Smaller and more durable (10,000 insertion cycles) than the existing mini-B connectors, the Micro-USB will also handle Power transfers, as well as Data. The USB Implementers Forum (USB-IF) has designed the Micro-USB to eliminate many of the proprietary Mini connectors found on different manufacturers digital devices, and it will be the standard USB connection on phones from the major cell phone manufacturers. USB 2.0 rated cable handles 480Mbps data transfer rates.

#### Features

- USB Universal / Reversible A Male to Micro-B Male
- Available in lengths up to 10 ft.
- 480Mbps USB 2.0 Data Transfer Rates
- Data and Power transference

# **Specifications**

| INPUT              |       |  |
|--------------------|-------|--|
| Cable Length (ft.) | 0.5   |  |
| Cable Length (m)   | 0.2   |  |
| Cable Length (in.) | 6     |  |
| Cable Length (cm)  | 15.24 |  |
| PHYSICAL           |       |  |
| Color              | Black |  |
|                    | 1/2   |  |



| ENVIRONMENTAL                       |                           |  |
|-------------------------------------|---------------------------|--|
| Operating Temperature Range         | -10/+75° C (14 to 167° F) |  |
| Storage Elevation (ft.)             | -20/+80° C (-4 to 176° F) |  |
| Storage Elevation (m)               | -20/+80° C                |  |
| CONNECTIONS                         |                           |  |
| Side A - Connector 1                | REVERSIBLE USB A (MALE)   |  |
| Side B - Connector 1                | MICRO-USB B (MALE)        |  |
| WARRANTY                            |                           |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |  |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Cables / IEEE 1394 Cables category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below :

68768-0173 FNY-W6003-01 88764-0800 13805532 148700-1 17-200621 17-250051P 954 AC102012-2 IP-USB1(C10)S-RW CABLE/RTP/USB/DT 0847290003 10115240-12200LF RS232-GTD USBFTVX2SA2N03A USBFTV2SA2N03A 1689404-1 FTP-629Y401 FTP-628Y402 943301-001 FNY-W6022 FNY-W6003-03 1310-1015-05 1310-1018-04 1310-1019-04 0887283402 UA-30AMFM-SL7B02 UA-30AMFM-SL7B01 UA-30AFM-LD7B03 UA-30AMFM-SL7B03 USBAPSCC7202A UES-1001A160 UES-1003A160 USBFTVX7SA2N20A USBFTVX2SA2N20A USBFTV2PEMSA2N10A FTP-629Y602 USBCAMCM100 USB A/F\*2 to 2.54 2\*5P-SH L=400mm EP-CBUSB10P2FLT 1310-1033-01 1310-1037-04 ASR-USB 68784-0075 17-241361 17-230471 217B-BC02 USB-29 19800-010500-200-RS USB+MINI DIN 6P WITH BKT