

J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

TERMINAL PART NUMBER	STO-2.5-250N
STRIP LENGTH (MM)	6.0

APPLICABLE WIRE SIZE	CONDUCTOR BARREL		INSULATION BARREL		TENSILE (NEWTONS)
	HEIGHT	WIDTH	HEIGHT	WIDTH	
1.0 mm ²	1.70	2.80	*	4.50	RE:BS5057
1.5 mm ²	1.80	2.80	*	4.50	RE:BS5057
2.5 mm ²	1.95	2.80	*	4.50	RE:BS5057

COMMENTS:

* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

GENERAL TOLERANCE:

CONDUCTOR HEIGHT	- +/- 0.05
CONDUCTOR WIDTH	- +/- 0.05
INSULATION HEIGHT	- N/A
INSULATION WIDTH	- +/- 0.10

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

Prepared by:	Approved by:
AJS	MS
29-01-01	29-01-01

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for jst manufacturer:

Other Similar products are found below :

B02B-JWPF-SK-R B3B-ZR B4B-ZR B5B-XH-A B5B-ZR B5PS-VH B6B-ZR-SM4-TF B6P-VH B7B-XH-A B8B-XH-A B8B-ZR B8P-VH BM02B-SRSS-TB BM06B-SRSS-TB BM10B-SRSS-TB B04P-NV B2B-PH-K-S B2B-ZR-SM4-TF B34B-PHDSS-B(LF)(SN) B3B-ZR-SM4-TF B5B-ZR-SM4-TF B6B-XH-A B6PS-VH B7B-ZR-SM4-TF B7PS-VH B8B-ZR-SM4-TF B8PS-VH BM04B-SRSS-TB BM05B-SRSS-TB IDH-KR-12 WC-ZE2426 WC-691 B6PS-VH(LF)(SN) FNGS12-6 TWE0.5-8 WC-GVH2630 WC-PUD2 S10B-PH-SM4-TB(LF)(SN) B2B-EH-A-TW (LF)(SN) B4B-EH-A-TW (LF)(SN) B4B-XH-TW (LF)(SN) B6B-EH-A-TW (LF)(SN) B8B-XH-TW (LF)(SN) B9B-XH-A BM02B-GHS-TBT BM03B-GHS-TBT BM04B-GHS-TBT BM06B-GHS-TBT BM08B-GHS-TBT BM08B-SRSS-TB