



Data Sheet

Type Number: 55620

Sytem: Nickel Metal Hydride/

KOH Electrolyte

Nominal Voltage [V]: 1.2

Nominal Capacity C [mAh]: 200

Typical Capacity C [mAh]: 210

at 40 mA / 1.00 V

Weight, approx. [g] 7

 Dimensions [mm]:
 min.
 max.

 Length [l]:
 13.9
 14.1

 Width Facing [w]:
 25.4
 25.6

 Height [h]:
 7.1
 7.4

UL Recognition: MH 13654 (N)

Coding: Manufacturing 5 digit code

(123 = day/4 = year/5 = version)

 Temperature Ranges [°C]
 min.
 max.

 Storage: less than 30 days
 -40
 65

 Discharge:
 -20
 65

 Charge:
 0
 65

Charging Method:

Normal Charging: 20 mA for 14 - 16 h Accelerated Charging (20 °C): 40 mA for 7-8 h

Time controlled, voltage control recommended

Fast Charging N/A

Trickle Charging: 6 mA

Overcharge (20 °C): 20 mA continuous

40 mA up to 1 year

Charge Retention [%] at 20 °C:

Capacity available after 1 month Storage at 20 $^{\circ}\!\text{C}$

Internal Resistance [Ohm]: 0.8

at charged cells, 20 °C, DC: 0.2 CA/2 CA, (IEC 61951-2)

Impedance [Ohm]: 0.14

at charged cells, 20 °C, AC: 1kHz, (IEC 61951-2)

Typical Capacities [mAh]:

at 200 mA / 0.90 V 90

Max. Discharge Current (cont.) [mA]: 300

Life Expectancy (typical):

IEC Cycle:1000 CyclesTrickle Charge:up to 6 years (20 ℃)Trickle Charge:up to 3 years (45 ℃)

Capacities based on normal charging, 20 ℃

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for varta manufacturer:

Other Similar products are found below:

56456 702 099 18750 4114 210 501 4610 726 406 4122 210 511 LCD-CHARGER + 4XAA 2400MAH 449915B 4607 726 406
55171403014 55625603059 55615602940 4112101411 4 022 211 111 4 106 101 436 4 020 211 111 MINI CHARGER + 2XAA 2100MAH
MINI-CHARGER 17730 LCD-SMART-CHARGER 414086X POCKET-CHARGER + 4XAA 2100MAH 458980A LCD MULTI
CHARGER CG511-150-PB EE UNIVERSAL CHARGER CG401D-050-PB CG511-050-PB CU303-018-PB CG381D-G-100-PB 413675G
CU202-030-PB 55615603059 CG381D-G-150-PB CG481G-050-PB CU303-030-PB CG511D-030-PB CA317-PB CG511D-100-PB
CU201G-B-030-PB 095668F 4600 726 406 CG511-030-PB CA418-PB CG481G-030-PB CG511D-150-PB CG381D-G-050-PB CU302030-PB CG341-030-PB CU201G-B-050-PB CA089-PB