

318-60151



**Article Number:** 318-60151

**Heat Shrink Tubing, 4FT-Stick, Adhesive Lined, 3:1, 3/16", 4.8/1.5 dia., Polyolefin, Black, 20/pkg**



Download spec sheet

## Base Data

**Local Order Number** 318-60151

**Type** TAN33-ST-4.8/1.5 BK

**Color** Black (BK)

- Features and Benefits**
- Adhesive lining provides an excellent seal against moisture and humidity.
  - 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters, while thin exterior wall is very flexible and provides superior insulation.
  - Meets UL224 VW-1 specifications making it ideal high heat applications (excludes clear tubing).
  - Polyolefin material provides mechanical strength with good resistance to solvents, oils and fuels.

**Product Description** TAN33 is a flexible, thin wall adhesive lined heat shrink tubing with highly flame retardant properties. The 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters. The adhesive lining begins to activate as the temperature reaches 176° F (80° C), to create a strong seal against moisture and humidity. 4-foot sticks are individually labeled for retail.

**Short Description** Heat Shrink Tubing, 4FT-Stick, Adhesive Lined, 3:1, 3/16", 4.8/1.5 dia., Polyolefin, Black, 20/pkg

## Product Dimensions

**Length L (Imperial)** 4.0 ft

**Length L (Metric)** 1.22 m

**Printable (Yes/No)** No

**Shrink Ratio** 3:1

**Tensile Strength (MPa)** 12 MPa

**Trade Size** 3/16 "

**Variant** Thin-Wall

**Volume Resistance (Ohm cm)** 10<sup>11</sup> Ω cm

**Nominal Diameter (Imperial)** 3/16 "

**Nominal Diameter (Metric)** 4.8 mm

**Wall Thickness WT (Imperial)** 0.039 "

**Wall Thickness WT (Metric)** 1.00 mm

**Recovered Diameter d (metric)** 1.5 mm

**Recovered Diameter d (imperial)** 0.059 "

**Supplied Diameter D (metric)** 4.8 mm

**Supplied Diameter D (imperial)** 0.189 "

## Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 20

## Material and Specifications

---

<b>Material</b>	Polyolefin, cross-linked (PO-X)
<b>Material Shortcut</b>	PO-X
<b>Elongation at break</b>	400%
<b>Halogenfree</b>	No
<b>Shrink Temperature</b>	+212 °F (+100 °C)
<b>Operating Temperature</b>	-67°F to +257°F (-55°C to +125°C)
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)