

This document was generated on 04/30/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>76155-3607</u>		
Status:	Active		
		Connector and Cable Assembly System	N. H. L. L.
Description:		4 Pair Vertical Backplane Header, Left Guided, Open Endwall, 16	1 Martin Adda to the second
		its, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm,	
	Lead-Free	,	
Documents: 3D Model		Application Specification AS 76060 000 (PDE)	
Drawing (PDF)		<u>Application Specification AS-76060-990 (PDF)</u> RoHS Certificate of Compliance (PDF)	Serie
U (n PS-76060-999 (PDF)		image - Reference only
Floduct Opecification	<u> </u>		inage - Reference only
Agency Certifica	ation		EU RoHS China RoHS
UL		E29179	ELV and RoHS
			Compliant
General			REACH SVHC
Product Family		Backplane Connectors	Not Reviewed
Series		<u>76155</u>	Low-Halogen Status
Application		Conventional	Low-Halogen
Application Tooling I	Documents	TM-622018799	Need more information on product
Component Type		PCB Header	environmental compliance?
Overview		Impact [™] Backplane Connector and Cable Assembly	
		<u>System</u>	Email productcompliance@molex.com
Product Name		Impact™	For a multiple part number RoHS Certificate
UPC		800756957074	Compliance, <u>click here</u>
Physical			Please visit the <u>Contact Us</u> section for any
Circuits (Loaded)		192	non-product compliance questions.
Circuits (maximum)		192	
Color - Resin		Black	
Durability (mating cy	cles max)	200	
First Mate / Last Bre	ak	No	Search Parts in this Series
Flammability		94V-0	76155Series
Guide to Mating Par	t	Yes	
Keying to Mating Pa		None	Mates With
Material - Metal		High Performance Alloy (HPA)	
Material - Plating Ma	ıting	Gold	<u>76160</u> Impact [™] 100 Ohm Daughtercard
Material - Plating Te	rmination	Tin	
Material - Resin		High Temperature Thermoplastic	Application Tooling FAQ
Net Weight		7.315/g	Tooling specifications and manuals are
Number of Columns		16	found by selecting the products below.
Number of Pairs		4	Crimp Height Specifications are then
Number of Rows		12	contained in the Application Tooling
Orientation		Vertical	Specification document.
PC Tail Length		1.40mm	Global
PCB Locator		No	Description Product #
PCB Retention		Yes	Backplane Insertion <u>0621005800</u>
PCB Thickness - Re	commended	1.00mm	Tool for Signal
Packaging Type		Tray	Contact
Pitch - Mating Interfa	ice	1.90mm	Backplane Module 0622018644
Pitch - Termination I		1.90mm	Installation Press-In
Plating min - Mating		0.762µm	
Polarized to PCB		Yes	Backplane Header 0621009610
Temperature Range	- Operating	-55°C to +85°C	Removal Tool for
Termination Interfac		Through Hole - Compliant Pin	GbX-U™, I-Trac™,
			Impact™, or TinMan

Electrical

Current - Maximum per Contact	
Data Rate	
Impedance	
Shield Type	
Shielded	
Voltage - Maximum	

Material Info

Reference - Drawing Numbers

Application Specification Product Specification Sales Drawing Symbol/Footprint Data

AS-76060-990 PS-76060-999 SD-76155-002 SYM-76155-3607

30V AC (RMS)/DC

0.75A 25.0 Gbps 100# N/A No

This document was generated on 04/30/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN 41612 Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

09231126901 PCN10F-24P-2.54DS(72) 004.767 02221602702 024069 602427301412000 013275 691327-1 74670-0732 74680-0340 75880-0015 76453-0014 86093159ALF 923454 QLC260R 120X10099X 120X10019X 120X10089X 120X10129X 121A10039X 121A10309X 122A10019X 122A10029X 122A10249X 122A10669X 122A11089X 122A13089X 122A10089X 122A10129X 122A10349X 122A13359X 1377391-4 DIN-048CPC-SR1-MH 1393583-2 1393726-7 140X10059X 140X10129X 143-1913-000 143-1908-000 1484472-1 173052 2110070-1 2110070-2 CBC20T00-008FDS5-0-1-002VR 983-0SE12-12P6 17041102202 172699-5036 173051 20 8457096 010 025 208458096005133