



## **Data Sheet**

Type Number: 55602

System: Nickel Metal Hydride/

KOH Electrolyte

Nominal Voltage [V]: 1.2

Nominal Capacity C [mAh]: 15

Typical Capacity C [mAh]: 16

at 3 mA / 1.00 V

Weight, approx. [g] 1.3

 Dimensions [mm]:
 min.
 max.

 Diameter [d]:
 11.4
 11.5

 Height [h]:
 2.9
 3.1

UL Recognition: MH 13654 (N)

Coding: Manufacturing 5 digit code

(123 = day/4 = year/5 = version)

 Temperature Ranges [°C]
 min.
 max.

 Storage: less than 30 days
 -40
 65

 Discharge:
 -20
 65

 Charge:
 0
 65

**Charging Method:** 

Normal Charging: 1.5 mA for 14 – 16 h
Accelerated Charging (20° C): 3 mA for 7-8 h
Fast Charging: 7.5 mA for 3 h \*

Time controlled, voltage control recommended

Trickle Charging: 0.45 mA

Overcharge (20°C): 2 mA continuous

3 mA up to 1 year

Charge Retention [%] at 20°C: 90

Capacity available after 1 month Storage at 20°C

Internal Resistance [Ohm]: 4

at charged cells, 20°C, DC: 0.2 CA/2 CA, (IEC 61951-2)

Impedance [Ohm]: 0.49

at charged cells, 20°C, AC: 1kHz, (IEC 61951-2)

Typical Capacities [mAh]:

at 15 mA / 0.90 V 15

Max. Discharge Current (cont.) [mA]: 30


Life Expectancy (typical):

IEC Cycle: 1000 Cycles

Trickle Charge: up to 6 years (20°C)

Trickle Charge: up to 3 years (45°C)

Capacities based on normal charging



 $<sup>^{\</sup>ast}$  for fully discharged cells, 20  $^{\circ}\text{C}$ 

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for varta manufacturer:

Other Similar products are found below:

56456 702 099 18750 4114 210 501 4610 726 406 4122 210 511 LCD-CHARGER + 4XAA 2400MAH 449915B 4607 726 406
55171403014 55625603059 55615602940 4112101411 4 022 211 111 4 106 101 436 4 020 211 111 MINI CHARGER + 2XAA 2100MAH
MINI-CHARGER 17730 LCD-SMART-CHARGER 414086X POCKET-CHARGER + 4XAA 2100MAH 458980A LCD MULTI
CHARGER CG511-150-PB EE UNIVERSAL CHARGER CG401D-050-PB CG511-050-PB CU303-018-PB CG381D-G-100-PB 413675G
CU202-030-PB 55615603059 CG381D-G-150-PB CG481G-050-PB CU303-030-PB CG511D-030-PB CA317-PB CG511D-100-PB
CU201G-B-030-PB 095668F 4600 726 406 CG511-030-PB CA418-PB CG481G-030-PB CG511D-150-PB CG381D-G-050-PB CU302030-PB CG341-030-PB CU201G-B-050-PB CA089-PB