



HUMIDITY



TEMPERATURE



FLOW



CONDUCTIVITY

MK33-W

Capacitive Humidity Sensor

Optimal for oil measurement applications




INNOVATIVE SENSOR TECHNOLOGY

Benefits & Characteristics

- High chemical resistance
- Wide temperature range
- Condensation resistant
- Fast recovery time
- Very low drift
- High humidity stability
- Suitable for extreme environments
- Customer specific sensor available upon request

Illustration¹⁾



1) For actual size, see dimensions

Technical Data

Dimensions (L x W x H / H2 in mm):	SIL	10.8 x 3.81 x 0.4 / 1.2
	Au/Cu-wire	10.8 x 3.81 x 0.4 / 0.8
Operating humidity range:	0 % RH to 100 % RH (maximal dew point +95 °C)	
Operating temperature range:	-40 °C to +190 °C	
Capacitance (C ₃₀):*	300 pF ±40 pF (at 30 % RH and +23 °C)	
Sensitivity (at C ₃₀ = 300 pF):	0.45 pF/% RH (15 % RH to 90 % RH)	
Loss factor:	< 0.01 (at 23 °C, at 10 kHz, at 90 % RH)	
Linearity error:	< 2 % RH (15 % RH to 90 % RH at +23 °C after one point calibration)	
Hysteresis:	< 2 % RH	
Response time t ₆₃ :	< 6 s (50 % RH to 0 % RH at +23 °C)	
Temperature dependence (typical):	$\Delta \% RH = (B1 \times \% RH + B2) \times T [^\circ C] + (B3 \times \% RH + B4)$ B1 = 0.0011 [1/ °C] B2 = 0.0892 [% RH/ °C] B3 = -0.0268 B4 = -2.079 [% RH]	
Measurement frequency:	1 kHz to 100 kHz (recommended 10 kHz)	
Maximal supply voltage:	< 12 V _{pp} AC	
Signal form:	alternating signal without DC bias	
Connection:*	CuP-SIL-wire post-plated with Sn, 10 mm or Au/Cu-wire, Ø 0.4 mm	

* Customer specific alternatives available

The calibration of the sensor must be done 5 days after soldering at the earliest.



HUMIDITY



TEMPERATURE



FLOW



CONDUCTIVITY

MK33-W


Capacitive Humidity Sensor

Optimal for oil measurement applications



INNOVATIVE SENSOR TECHNOLOGY

Characteristic Curve



Order Information - SIL (CuP-SIL-wire post-plated with Sn, 10 mm)

Order code	MK33 (300pF ±40pF) 040.00192
------------	---------------------------------

Order Information - Au/Cu-wire, Ø 0.4 mm

Order code	MK33-W (300pF ±40pF) 040.00180
------------	-----------------------------------



INNOVATIVE SENSOR TECHNOLOGY

Innovative Sensor Technology IST AG, Stegrütistrasse 14, CH-9642 Ebnat-Kappel, Switzerland,
Phone: +41 (0) 71 992 01 00 | Fax: +41 (0) 71 992 01 99 | E-mail: info@ist-ag.com | Web: www.ist-ag.com



All mechanical dimensions are valid at 25 °C ambient temperature, if not differently indicated • All data except the mechanical dimensions only have information purposes and are not to be understood as assured characteristics • Technical changes without previous announcement as well as mistakes reserved • The information on this data sheet was examined carefully and will be accepted as correct; No liability in case of mistakes • Load with extreme values during a longer period can affect the reliability • The material contained herein may not be reproduced, adapted, merged, translated, stored, or used without the prior written consent of the copyright owner • Typing errors and mistakes reserved • Product specifications are subject to change without notice • All rights reserved

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board Mount Humidity Sensors](#) category:

Click to view products by [1st Innovative Sensor](#) manufacturer:

Other Similar products are found below :

[HSHCAA114A](#) [SI7020-A10-IM](#) [SI7020-A20-IMR](#) [SI7023-A20-IM1R](#) [SI7021-A20-YM0](#) [SI7021-A20-IMR](#) [SI7013-A10-IM1](#) [SI7021-A20-IM1R](#) [SI7007-A20-IMR](#) [SI7021-A10-IM1](#) [LCSC-20S-B](#) [LCSC-30S-B](#) [LCSC-30S-MD](#) [LCSC-30S-ML](#) [LCSC-30S-HX](#) [LCSC-SHT30S-JCB](#) [LCSC-30S-HE](#) [LCSC-30S-HERS](#) [LCSC-30S-B-550-XDG](#) [TH30S-B](#) [CFSTM-UB3-U](#) [MGS-2-01](#) [HPP845E031R4](#) [HPP845E131R5](#) [MGS-3-01](#) [HTU21D](#) [CC2D35S-SIP](#) [CC2D33S-SIP](#) [CC2D33-SIP](#) [CC2D23S-SIP](#) [CC2D23-SIP](#) [251-10509](#) [HDC1050DMBR](#) [HIH6131-021-001](#) [HIH-4000-004](#) [HIH-4000-002](#) [HIH7120-021-001](#) [HIH6130-021-001](#) [SI2144-A20-GMR](#) [SI5332DC09118-GM1](#) [HIH-4031-001S](#) [SHT35-DIS-F2.5kS](#) [HIH-4020-003](#) [HIH-4031-003S](#) [SHT30-DIS-F2.5kS](#) [HDC2010YPAR](#) [HDC2010YPAT](#) [HIH-4030-003S](#) [HIH-4030-001S](#) [SI7006-A20-IMR](#)