
.050" Surfacemount Socket .276" and .315" Mating Heights

**P50L Series** 



- Low profile 0.276" 0.315" (7-8 mm) addresses surfacemount board stacking applications
- High temperature insulator compatible with IR and wave soldering
- Solder brackets increase connector stability to protect contact solder joint integrity
- Polarized alignment posts ensure correct mating
- RoHS Compliant. See the Regulatory Information Appendix (RIA) in the "RoHS Compliance" section of www.3Mconnector.com for compliance information (RIA E1 and C1 apply)

Date Modified: February 17, 2010

TS-2055-B Sheet 1 of 2

## **Physical**

#### **Insulator:**

Material: Glass Filled PPS

Flammability: UL 94V-0

Color: Brown

Contact Material: Phosphor Bronze

#### **Plating:**

Underplating: Nickel

Wiping Area: Gold Flash

Solder Tails: Gold Flash

Retaining Clips: Tin-Copper

Mating Compatibility: TS-2056

### **Electrical**

**Current Rating:** 0.5 A

**Insulation Resistance:**  $> 1 \times 10^9 \,\Omega$  at  $500 \,V_{DC}$ **Withstanding Voltage:**  $650 \,V_{AC}$  for 1 minute

#### **Environmental**

**Temperature Rating:** -55°C to +85°C

**Process Rating:** 260°C MSL1 (per J-STD-020C)

UL File No.: E68080

.050" Surfacemount Socket .276" and .315" Mating Heights

#### **Product Table / Dimensions** Contact **Printed Circuit Board Layout** D Quantity (Component Side View) 24.03 21.03 17.03 14.23 13.43 14.23 11.43 \*Ref. $\phi$ 1.9±0.05 [0.946][0.828][0.670][0.560][0.529][0.450][0.560](0.075±0.002) B±0.1(B±0.004) 30.38 27.38 23.38 20.58 19.78 17.78 φ1.6±0.05 F±0.1(F±0.004) 30 [1.196][1.078] [0.920][0.810][0.779][0.700](0.063±0.002) Ref. $\phi$ 1.4±0.05 0.8±0.05 1.27±0.05 (0.031±0.002) (0.055±0.002) 4±0.05 36.73 33.73 29.73 26.93 26.13 24.13 26.93 (0.157±0.002) $\phi$ 1.1+0.05 40 (0.050±0.002) [1.060] [1.029] [0.950] [1.060] (0.043±0.002) [1.446] [1 328] [1.170] 43.08 40.08 36.08 33.28 32.48 30.48 33.28 50 [1.696][1.578][1.420][1.310][1.279][1.200][1.310]49.43 46.43 42.43 39.63 38.83 36.83 39.63 60 [1.946][1.828] [1.670][1.560][1.529][1.450][1.560]2.2±0.05 0.087±0.002) 62.13 59.13 55.13 52.33 51.53 49.53 52.33 80 [2.446] [2.060] [2.029] [2.060] [2.328][2.170][1.950]74.83 71.83 67.83 65.03 64.23 62.23 65.03 100 [2.946][2.828][2.670][2.560] [2.529][2.450][2.560]=Polarity identification 87.53 84.53 80.53 77.73 76.93 74.93 77.73 "n" is number of contacts. 120 [3.446][3.328][3.170][3.060][3.029][2.950][3.060] \* 1.9 and 1.4 are the recommend hole sizes when using automated placement equipment. Precision of the placement equipment should be considered. A Type (Standoff height) B Type В X-X' Cross Section 1.27(0.050) pitch\_ \$ .25(0 3(0.118) Standoff height Polarity identification А Туре B Type 0.4(0.016) $\overline{\phi}$ 1.6(0.063) 0.4(0.016) Y-Y' Cross Section $\phi$ 1.1(0.043) 10.25(0.404) 10.25(0.404) 6.6(0.260) 6.6(0.260) A Type В Туре **Ordering Information** P50L - XXXS - XX - DA (RIA E1 and C1 apply) Contact Quantity: AS = SMT, Type A See Table BS = SMT, Type B TS-2055-B Sheet 2 of 2

# **Important Notice** All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M. Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. 3M MAKES NO OTHER WARRANTIES

INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of

3M is a trademark of 3M Company.

the legal theory asserted.

6801 River Place Blvd. Austin, TX 78726-9000

www.3Mconnector.com

U.S.A. 1-800-225-5373

**3M Electronics Solutions Division** 

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Rack & Panel Connectors category:

Click to view products by 3M manufacturer:

Other Similar products are found below:

00170420102 00171420202 00171440002 008026165000265 00-8219-072-000-112P44 008219072000112P5 008219072000112P61 00-8223-096-580-102 02-014-013-5200-000 00-8129-015-610-108 613467-000 CTJ112E01E-513 CTJ116E03A-513 M81714/63-22S L/C M81714/65-12-1 66020-2 CW8958-000 699886-000 D250-50632 70.400.3240.0 70.955.2453.3 733753-000 F22831-000 780-522-DPX34RG8-02 MMA25-0051R1 MMA25-0341D1 8660-501 87.060.0053.0 900709N001 QRP4-12P-C(01) QR/P6-6S-C(01) AC-600003-004 1218600-1 D-659-0061 DMC-MD 24 C-T 1-445717-6 1484398-2 1484399-2 1484469-2 MR-34MG 1484225-1 1484398-1 1484510-4 1604997-2 1663130-1 1663767-7 1663767-8 MTC100-BF1-P31CS015 MTC100-KT2-0083 MTC100-KT2-0123-003