
	TECHNICAL DATA SHEET	code	MRG1781
		version	1
		date	2006-07-11
	Coax RG178 PE PVC	page	1/2

APPLICATION

Coaxial communication cable based on MIL-C-17.

CONSTRUCTION




1	Inner conductor	Silver plated, copper clad steel
2	Dielectric	Solid PE
3	Braid	Tinned copper
4	Sheath	PVC according the European Standard HD 624.

REQUIREMENTS AND TEST METHODS

Test methods in accordance with European standard EN 50289.

Mechanical characteristics

1. Inner conductor:		7 x 0.1 mm
Diameter:		0.3 mm ± 0.02 mm
2. Dielectric:		
Diameter:		0.84 mm ± 0.15 mm
3. Outer conductor:		
Diameter screen:		1.37 mm ± 0.15 mm
Coverage braid:		95 % ± 4 %
4. Sheath:		
Diameter:		1.8 mm ± 0.1 mm
5. Cable:		
Storage/operating temperature:		-25°C to +70°C
Minimum installation temperature:		-5 °C
Total weight:		8.5 g/m

	TECHNICAL DATA SHEET	code	MRG1781
		version	1
		date	2006-07-11
	Coax RG178 PE PVC	page	2/2

Electrical characteristics

Mean characteristic impedance:	$50 \pm 2 \Omega$
Regularity of impedance:	> 40 dB
DC resistance inner conductor:	$\leq 802 \text{ Ohm/km}$
Capacitance:	$100 \text{ pF/m} \pm 3 \text{ pF/m}$
Nominal velocity of propagation:	66 %
Voltage Rating	
DC:	1.0 kVdc
RMS	0.6 kVrms

Nominal Attenuation:

10 MHz:	19 dB/100m
200 MHz:	63 dB/100m
400 MHz:	92 dB/100m
1000 MHz:	151 dB/100m



Belden CDT believes this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [belden manufacturer](#):

Other Similar products are found below :

[HIPWP2LA](#) [8916-BRN-100](#) [8916-GRN/YEL-500](#) [8916-YEL-500](#) [8918-GRY-1000](#) [8919-DK-BLU-100](#) [5T00UP 008500](#) [7810A-BLK-500](#)
[7860NBH](#) [7934A-BLK-1000](#) [7937A-BLK-1000](#) [8019-100](#) [8058](#) [8080](#) [8108-060-1000](#) [8125-CHR-100](#) [8132-CHR-1000](#) [8133-CHR-1000](#)
[8155-CHR-1000](#) [8162-060-1000](#) [8162-CHR-1000](#) [8164-CHR-100](#) [8164-CHR-1000](#) [8185-CHR-100](#) [8205-CHR-1000](#) [8221-BLK-1000](#) [8233-](#)
[010-1000](#) [8233-BLK-1000](#) [8237-BLK-500](#) [8238-BLK-500](#) [8241A-BLK-1000](#) [8241F-RED-MATTE-1000](#) [8263-BLK-U1000](#) [8279-BLK-](#)
[1000](#) [8281-003-1000](#) [8281 010500](#) [83002 0101000](#) [83003-006-500](#) [83007 0081000](#) [83008 0091000](#) [83010-RED-100](#) [83029 0021000](#) [8302-](#)
[CHR-500](#) [8303 060500](#) [8307-CHR-100](#) [8310-060-1000](#) [8310-CHR-1000](#) [83305E 009100](#) [83347E 009100](#) [8348-060-500](#)