

## Application

- Horizontal and building backbone cable.
- Support current and future **Category 6 and Category 5 enhanced** applications, such as: 10 Base-T, 100 Base-T, 1000 Base-T (Gigabit Ethernet), FDDI, ATM

## Key features and Standards

- General standards: **ISO/IEC 11801 2<sup>nd</sup> edition (2002)**, **EN 50173 2<sup>nd</sup> edition (2001)**, **ANSI/TIA/EIA 568-b.2 (2002)**

## Construction & Dimensions



- Construction: Unshielded 4 twisted pairs
- Conductor: solid bare copper
- Conductor diameter: AWG 23 (0,57 mm)
- Conductor insulation material: Polyolefine
- Diameter over insulation: 1,01 mm
- Cross web: FRNC compound
- Jacket material: FRNC compound
- Outer diameter: 6,20 mm

Pair 1	White-Blue/Blue
Pair 2	White-Orange/Orange
Pair 3	White-Green/Green
Pair 4	White-Brown/Brown

Colour identification according to IEC 60304

## Electrical characteristics (at 20 °C)

Nominal mutual capacitance at 1 kHz	50 nF/km
Maximum conductor DCR	70 Ohm/km
NVP - Nominal Velocity of Propagation	0.70 c
SKEW – Propagation delay difference (100 MHz)	typical $\leq 15$ ns/100m
Mean Characteristic Impedance 4-100 MHz <sup>1)</sup>	100 $\pm$ 5 Ohm

<sup>1)</sup>: According to cable requirements of ISO/IEC 11801 category 6, Sept. 2002.

## General and environmental characteristics

Temperature range - operation	-20°C - +60°C
Temperature range - installation	+0°C - +50°C
Minimum bending radius - operation	25 mm
Minimum bending radius - installation	50 mm
Maximum pulling tension	80 N
Flame retardancy	IEC 332-1
Caloric value	480 kJ/m
Weight (approx.)	43.9 kg/km
Maximum operating voltage	48 V rms
Maximum continuous current per conductor (25°C)	1.4 A

### Electrical characteristics (at 20 °C)

#### Attenuation

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Max.) <sup>1)</sup>	-	4.0	6.0	7.6	8.5	10.8	15.5	19.9	25.3	29.2	33	dB/ 100m
Typical	[1.7]	3.5	5.6	7.1	8.0	10.1	14.4	18.6	23.6	27.0	30.7	dB/ 100m

#### NEXT (Near end crosstalk)

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	66	60	57	56	53	48	45	42	41	39	dB/ 100m
Typical	[76]	73	66	64	63	56	55	52	49	48	45	dB/ 100m

#### Power sum NEXT

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	63	57	54	53	50	45	42	39	38	36	dB/ 100m
Typical	[74]	71	64	62	61	54	53	50	47	46	43	dB/ 100m

#### Power sum ELFEXT

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	53	45	41	39	35	29	25	21	19	17	dB/ 100m
Typical	[70]	64	57	51	49	45	39	35	31	29	27	dB/ 100m

#### ACR

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	62.0	54.0	49.4	47.5	42.2	32.5	25.1	16.7	11.8	6.0	dB/ 100m
Typical	[74]	70	60	57	55	46	41	33	25	21	14	dB/ 100m

#### Power sum ACR

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	59.0	51.0	46.4	44.5	39.2	29.5	22.1	13.7	8.8	3.0	dB/ 100m
Typical	[72]	68	58	55	53	44	39	31	23	19	12	dB/ 100m

#### Return Loss

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	23.0	25.0	25.0	25.0	23.6	21.5	20.1	18.8	18.0	17.3	dB/ 100m
Typical	[33]	36	44	42	40	38	36	31	27	25	24	dB/ 100m

<sup>1)</sup>: Specification values according to cable requirements of ISO/IEC 11801 category 6, Sept. 2002.

Note: Values between brackets are for information only

### Ordering information

#### MARKING

Text on the cable jacket                      Inkjet printing

**BELDEN 7965ENH UTP CAT6 4PR AWG23 LSNH ISO/IEC 11801 EN50173 VERIFIED 100 OHM**

Meter marking:                                      Yes

#### JACKET COLOUR

Colour	RAL code
Blue	RAL 5015

#### PACKAGING (PUT UP)

500m and 1000m Crate reels

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [belden](#) manufacturer:*

Other Similar products are found below :

[HIPWP2LA](#) [8916-BRN-100](#) [8916-GRN/YEL-500](#) [8916-YEL-500](#) [8918-GRY-1000](#) [8919-DK-BLU-100](#) [5T00UP 008500](#) [7810A-BLK-500](#)  
[7860NBH](#) [7934A-BLK-1000](#) [7937A-BLK-1000](#) [8019-100](#) [8058](#) [8080](#) [8108-060-1000](#) [8125-CHR-100](#) [8132-CHR-1000](#) [8133-CHR-1000](#)  
[8155-CHR-1000](#) [8162-060-1000](#) [8162-CHR-1000](#) [8164-CHR-100](#) [8164-CHR-1000](#) [8185-CHR-100](#) [8205-CHR-1000](#) [8221-BLK-1000](#) [8233-](#)  
[010-1000](#) [8233-BLK-1000](#) [8237-BLK-500](#) [8238-BLK-500](#) [8241A-BLK-1000](#) [8241F-RED-MATTE-1000](#) [8263-BLK-U1000](#) [8279-BLK-](#)  
[1000](#) [8281-003-1000](#) [8281 010500](#) [83002 0101000](#) [83003-006-500](#) [83007 0081000](#) [83008 0091000](#) [83010-RED-100](#) [83029 0021000](#) [8302-](#)  
[CHR-500](#) [8303 060500](#) [8307-CHR-100](#) [8310-060-1000](#) [8310-CHR-1000](#) [83305E 009100](#) [83347E 009100](#) [8348-060-500](#)