

No. of Ways	Ordering code	A	B	C	D	E	F	Cable		Outlet	
								Round max.	Round min.	Flat max.	Flat min.
09	DS 09	32.2	22.1	25.0	38.5	15.0	28.6	6	4	-	-
15	DS 15	39.8	26.1	33.3	48.0	15.0	34.1	7	5	-	-
25	DS 25	54.2	30.3	47.0	63.0	15.0	38.3	8	6	-	-
37	DS 37	70.7	38.2	63.5	79.0	15.0	46.2	-	-	7X16	5X16
50	DS 50	68.0	38.2	61.1	76.5	18.0	46.2	-	-	10X16	5X16


Characteristics:

- * Facility for side & top cable entry.
- * External cable clamp can be used for top or side cable entry.
- * Available with slide lock with 2 screws for retaining connector.

Material:

Hood: Flame retardant thermoplastic.
Screws & Slide lock : steel, Zinc plated.

Computer4\productscon\ELECTRONICS\DhDCU

TOLERANCES UNLESS OTHERWISE SPECIFIED ±0.1	PLASTIC HOODS (FOR SLIDE LOCK)	DIMENSIONS IN MM	
		DATE	SIGN.
SCALE ~		DESIGN	08.04.10
		DRAWN	08.04.10
		CHKD.	
		APPD.	
		DRG. NO.	
		DHDCU-018. A4.	
		SHEET 1 OF 1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [mh connectors](#) manufacturer:

Other Similar products are found below :

[MHDCMR37-ULP](#) [C88E310000](#) [MHD45ZK25-DM25P-K](#) [MHCCOV-25SC-BK](#) [MHDTZK15-RA-K](#) [DSSKP15L-DB15S-K](#) [DSSKM15L-DB15S-K](#) [MHDM25-DM25P-K](#) [MHRJ126P4CR](#) [BNC4MML1MRG58](#) [RJ45SRB-RET-O](#) [MHDPPK25-Y-K](#) [MHCCOV-9ME](#) [BNCL2.0MRG58](#) [MHDD15-F-T-B-M](#) [MHDD9-M-T-B-M](#) [MHDM15-K](#) [MHDTZK25-K](#) [MHRJ126P6CR](#) [MHDM9-DB9P-K](#) [RJ45SRB-LGREY](#) [MHED-DS25S](#) [BNCL1.0MRG58](#) [MHDM25-K](#) [RG58SRB-G](#) [MHD45PK37-K](#) [MHDTPPK25-DB25SK](#) [MHDU45ZK09-K](#) [DA9-PMJ8-B-K](#) [MHD45ZK50-K](#) [MHDD25-M-T-B-S](#) [MHDB50SP](#) [MH3101S-8821](#) [RG58SRB-R](#) [MHRJ116P4CR](#) [MHTRI-M-9-K](#) [MHDD25-F-T-B-M](#) [MHDM9-DB9S-K](#) [MHDPPK-M-37-K](#) [MHDTPPK37-K](#) [DA9-SMJ8-R-K](#) [RG58SRB-BE](#) [MHDM25-DB25P-K](#) [GA0909FFLGK-RC](#) [MHCCOV-15SN-LG](#) [MHDTZK9-RA-K](#) [DSSKM25L-DB25P-K](#) [MHD45ZK9-DM9P-K](#) [MHDVSL25-K](#) [MHCCOV-25SC-LG](#)