

SAFETY DATA SHEET ULTRALUBE - AEROSOL

1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

PRODUCT NAME ULTRALUBE - AEROSOL
PRODUCT NO. EULL200D
APPLICATION Lubricant
SUPPLIER H K WENTWORTH PTY LIMITED
 P.O. BOX 339
 BROOKVALE, NSW 2100
 AUSTRALIA
 TEL: 02 9938 1566
 FAX: 02 9938 1467
 GENERAL MANAGER
EMERGENCY TELEPHONE Tel: 029938 1566 between 8.30am and 5.00pm EST

2 HAZARDS IDENTIFICATION

HAZARD ID

Extremely flammable.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

HAZARD ID 2

The above phrases are the risks associated with the product

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE (According to criteria of NOHSC). DANGEROUS GOODS (According to ADG Code).

SAFETY PHRASES

S16	Keep away from sources of ignition - No smoking.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
A1	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.
S2	Keep out of the reach of children

DG CLASS

Division 2.1: Flammable gases.

PACKING GROUP Not Applicable

UN NO. 1950

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
PENTANE	203-692-4	109-66-0	30-60%	F+;R12 Xn;R65 R66 R67 N;R51/53
1,1,1,2-TETRAFLUOROETHANE R134A	212-377-0	811-97-2	30-60%	-

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels Ingredients are registered on AICS

4 FIRST-AID MEASURES

NOTES TO THE PHYSICIAN

Treat symptomatically

ULTRALUBE - AEROSOL

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Get medical attention.

INGESTION

Immediately rinse mouth and provide fresh air.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers. Ventilate well.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Provide good ventilation.

STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
1,1,1,2-TETRAFLUOROETHANE R134A	ES-TWA	1000 ppm	4240 mg/m3		
PENTANE	ES-TWA	600 ppm	1770 mg/m3	750 ppm	2210 mg/m3

INGREDIENT COMMENTS

Australian exposure limits are: LT= ES-TWA and ST= ES STEL

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. DO NOT SMOKE IN WORK AREA!

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Aerosol Liquid

COLOUR Colourless

ODOUR Characteristic

PHYSICAL DATA COMMENTS Information given concerns the major ingredient.

VOLATILITY DESCRIPTION Volatile.

SOLUBILITY Immiscible with water

BOILING POINT (°C) 36

MELTING POINT (°C) -130

RELATIVE DENSITY 0.646 @ 20 °C

BULK DENSITY 646 kg/m3

VAPOUR PRESSURE 5.33 kPa @ 19 °C

FLASH POINT (°C) -48 CC (Closed cup).

AUTO IGNITION TEMPERATURE (°C) 309

FLAMMABILITY LIMIT - LOWER(%) 1.4

C)

ULTRALUBE - AEROSOL

FLAMMABILITY LIMIT - UPPER(%) 7.8

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SKIN CONTACT

Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin. Prolonged or repeated exposure may cause severe irritation.

EYE CONTACT

Irritating to eyes.

Other Health Effects

This substance has no evidence of carcinogenic properties.

ROUTE OF ENTRY

Inhalation.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	2.1		
PROPER SHIPPING NAME	AEROSOLS		
ADG CLASS			
Class 2.1: Flammable gases			
UN NO.	1950	UK ROAD PACK GR.	Not Applicable
ADR CLASS NO.	2.1	DG CLASS	Division 2.1: Flammable gases.
PACKING GROUP	Not Applicable	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	Not Applicable	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PACK GR.	Not Applicable
EMS	F-D; S-U	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1950
AIR CLASS	2.1	AIR PACK GR.	Not Applicable

15 REGULATORY INFORMATION

ULTRALUBE - AEROSOL

LABELLING



Extremely
Flammable



Dangerous for the
environment

RISK PHRASES

R12	Extremely flammable.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S16	Keep away from sources of ignition - No smoking.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
A1	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.
S2	Keep out of the reach of children

GUIDANCE NOTES

Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003 (1995)]

NATIONAL REGULATIONS

National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC:1005(1994)]

National Code of Practice for the Control of Workplace Hazardous Substances [NOHSC:2007(1994)]

National Code of Practice for the Preparation of Material Safety Datasheets [NOHSC:2011(2003)]

Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004) and List of Designated Hazardous Substances

POISONS SCHEDULE NUMBER none

16 OTHER INFORMATION

REVISION DATE NOVEMBER 2007

REV. NO./REPL. SDS GENERATED 0

SDS NO. 11481

RISK PHRASES IN FULL

R12	Extremely flammable.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [electrolube](#) manufacturer:

Other Similar products are found below :

[TCRGUNB](#) [ER2220RP250G](#) [GP300S](#) [GP500S](#) [HTCX35SL](#) [EAD200D](#) [PRS400D](#) [TPM350](#) [SCP26G](#) [2K300KIT](#) [DCT01L](#) [SWAJ05L](#)
[ARW300](#) [DCE0.75L](#) [GP300SL](#) [SSS500ML](#) [SYR20ML](#) [GP500SL](#) [ER2218RP250G](#) [ER2224](#) [UR5638](#) [CCRG01L](#) [SPG900G](#) [DEI05L](#)
[ER221935SL](#) [HTS100T](#) [ASA250ML](#) [HTC700G](#) [ULL200D](#) [EADI200D](#) [AFAG35SL](#) [ECW025](#) [EADPI200](#) [HTSP100T](#) [CMO200D](#) [FSC05L](#)
[HTC100T](#) [OSL400](#) [SYR02ML](#) [URC200D](#) [ER2223](#) [RST250](#) [SOB200D](#) [UR5118RP250G](#) [UR5528RP250G](#) [DDF400 ML](#) [NSCP400H](#)
[AFC400D/12](#) [SYR10ML](#) [DCA01L](#)