

MS206B

Pos-E-Kon™

Male screw terminal insert



General

Type:	16 A 600 VAC
T&B UPC:	78621011643
T&B Status:	M
Series:	B series
Flammability:	UL94 V-0
Approvals:	MEIE, EZU, SEV
Housing Temperature Range:	-40°C/-40°F to +125°C /+257°F
Insert Material:	Glass-filled thermoplastic
Insert Temperature Range:	-40°C/-40°F to +125°C /+257°F
Rated Voltage:	600 VAC
Screw Terminal:	20–14 AWG
Test Voltage:	3 kV eff.
Working Current:	16 A max.
Special Features:	IP65 locked positions per DIN VDE 0470, IEC 529
Material:	Die-cast aluminum alloy

Dimension Information

AWG:	20–14 AWG (0.5–2.5 mm ²)
Contact Material:	Solid drilled copper alloy
Contact Resistance:	# 1 milliohm
Contact Surface:	Hard silver plated, Hard gold plated
Contact Type:	6 contacts with ground connection
Crimp Terminal:	20–12 AWG
EPDM Seal Gaskets:	Epoxy powder-coat finish

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [abb](#) manufacturer:

Other Similar products are found below :

[TV10-516R](#) [017667013](#) [RF727](#) [2CMA100178R1000](#) [5SDD 92Z0401](#) [ESV14-BS](#) [EZS-21-250](#) [F204AC-40/0.03](#) [F362-25/0.03](#)

[GJL1211001R0011](#) [GJL1211201R8000](#) [GJL1211501R8000](#) [GJL1213001R0017](#) [GJL1213001R0101](#) [GJL1311001R0101](#) [GJL1311001R8010](#)

[GJL1311201R0001](#) [GJL1313001R0011](#) [GJL1313001R0101](#) [GJL1317201R0001](#) [AF09-30-01-11](#) [AF460-30-11-68](#) [1455](#) [EF45-30](#) [ERG297](#)

[HSC2-20](#) [1SAM201904R1001](#) [1SAM350000R1003](#) [1SAZ721201R1009](#) [1SAZ721201R1014](#) [1SAZ721201R1025](#) [1SFA611101R1002](#)

[1SFA611130R1103](#) [1SFA611131R1101](#) [1SFA611143R1101](#) [1SFA611202R1108](#) [1SFA611203R1108](#) [1SFA611215R1001](#)

[1SFA611216R1108](#) [1SFA611285R1002](#) [1SFA611702R6006](#) [1SFA616162R1025](#) [1SFA619100R3015](#) [1SVR730020R0200](#) [IPC4111](#)

[OS30FACC12](#) [OS60GJ03](#) [OVR1N160277PS](#) [OXC1L48](#) [254](#)