


Technical Data Sheet



PRODUCT DESCRIPTION:	Ferric Chloride	DATE:	03/97
PRODUCT CODE:	FCC	PAGES:	1

PRODUCT DESCRIPTION

A sealed packet of ferric chloride hexahydrate crystals for etching copper clad boards.

FEATURES

- * Does not absorb moisture quickly.
- * Easy and economic in use.
- * Safely packed and sealed in polythene bag.

APPLICATION

Dissolve the crystals in 250ml of warm water in a plastic or glass vessel, or in an etching tank. Stir to dissolve and agitate flow of solution over board being etched. Solution can be re-used and as it becomes weaker heating will increase it's life. Contents are sufficient for a total amount of 500ml (1 pint) of solution.

TYPICAL PROPERTIES

Specific Gravity:	1.66
Melting Point:	37°C
Solubility @ 20°C:	91.8g/100g water

PACKAGING

250g Packet

ORDER CODE

FCC250G

Copyright Electrolube 1997

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [electrolube](#) manufacturer:

Other Similar products are found below :

[TCRGUNB](#) [ER2220RP250G](#) [GP300S](#) [GP500S](#) [HTCX35SL](#) [EAD200D](#) [PRS400D](#) [TPM350](#) [SCP26G](#) [2K300KIT](#) [DCT01L](#) [SWAJ05L](#)
[ARW300](#) [DCE0.75L](#) [GP300SL](#) [SSS500ML](#) [SYR20ML](#) [GP500SL](#) [ER2218RP250G](#) [ER2224](#) [UR5638](#) [CCRG01L](#) [SPG900G](#) [DEI05L](#)
[ER221935SL](#) [HTS100T](#) [ASA250ML](#) [HTC700G](#) [ULL200D](#) [EADI200D](#) [AFAG35SL](#) [ECW025](#) [EADPI200](#) [HTSP100T](#) [CMO200D](#) [FSC05L](#)
[HTC100T](#) [OSL400](#) [SYR02ML](#) [URC200D](#) [ER2223](#) [RST250](#) [SOB200D](#) [UR5118RP250G](#) [UR5528RP250G](#) [DDF400 ML](#) [NSCP400H](#)
[AFC400D/12](#) [SYR10ML](#) [DCA01L](#)