

Tadiran High Power Lithium Organic Cell Model TLM-1550HP

1. Scope

This data sheet describes the mechanical design and performance of Tadiran high power lithium organic cell model TLM-1550HP.

2. Characteristics

2.1. Physical

2.1.1. Length: 50.2± 0.3 mm.
 2.1.2. Diameter: 15.0 mm. max.

2.1.3. Weight: 20 ± 0.2 gr.



2.2. Electrical

2.2.1. Discharge

Discharge capacity at 50mA @ RT 550mAh

Maximum discharge current: Continuous: 5.0 A

Pulse: 15 A

2.2.2. Operating Temperature range: -40° C to 85° C

2.2.3. Self discharge current:

Temperature	Self-discharge rate [µA]
22	[μΑ]
35	5
42.	5.5
55	6
72	10
85	TBD


2.2.4. Capacity loss 1st year: 40mAh
Annual capacity loss: 15mAh

2.2.5. Cell impedance: Less than 100 mOhm @ 1kHz at room temperature.




2.2.6. Performance Data:

Discharge capability at RT




Pulse capability at RT






Discharge capability @ 1A at several temperatures



The data for 85C is same as for 72C


Pulse capability @ 1A at several temperatures



The data for 85C is same as for 72C




Discharge capability @ 0.5A at several temperatures



The data for 85C is same as for 72C


Pulse capability @ 0.5A at several temperatures



The data for 85C is same as for 72C




Discharge capability @ 0.1A at several temperatures



The data for 85C is same as for 72C

Pulse capability @ 0.1A at several temperatures




The data for 85C is same as for 72C



End of life indication:

OCV measurements can provide a good estimation for the remaining capacity of the cell as shown below:

Capacity vs. OCV



Safety tests:

The cell has successfuly passed the following safety tests:

Short circuit at RT and at 55°C.

Oven at 150°C.

Impact.

Nail penatration.

Over charge and over discharge.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for tadiran manufacturer:

Other Similar products are found below:

 $TL\text{-}5242 \ TL\text{-}5104/SBP \ TL5902/T \ TL\text{-}5903/P \ TL\text{-}5930/F$