


DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	Jeff McVicker	DATE:	12/1/03
CHECKED BY:	Hisham Odish	DATE:	12/19/03
APPROVED BY:	John Cole	DATE:	1/21/04

DRAWING TITLE:		Retractable Sleeve 4mm Plug to Plug Lead, Red	
SIZE	DWG. NO.	ELECTRONIC FILE	
A	76-093	84N2135.dwg	
SCALE:		U.O.M.: Inches	
NTS		SHEET: 1 OF 1	

- Specifications:**
- Rating: 1,200V AC/DC, 12 amps
  - Internal Resistance: 15 milliohms
  - Operating Temp: -20°C to 80°C
  - Materials:
  - Cable Type: Flexible PVC, Conductor: 0.75mm<sup>2</sup>
  - Body: Polyamide (Nylon)
  - Plug: Bronze and Brass, Nickel Plated



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART, CAN BE REPRODUCED, WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

DCP #		REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1355		A	Released	JWM	12/1/03	HO	12/19/03	JC	1/21/04

DCP NO. SPC-F005 \* Effective: 7/8/02 \* DCP No: 1398

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [tenma](#) manufacturer:*

Other Similar products are found below :

[21-10164](#) [21-10158](#) [BC0024434](#) [72-7712](#) [76-009](#) [76-081](#) [CBB019217](#) [CBB018722](#) [72-9170](#) [72-13668](#) [72-13686](#) [72-13688](#) [72-13736](#) [72-13742](#) [72-13818](#) [72-13822](#) [72-13824](#) [72-13836](#) [72-13856](#) [72-13858](#) [72-13872](#) [72-13874](#) [72-13908](#) [72-13950](#) [72-13986](#) [72-14060](#) [72-14302](#) [72-3099](#) [76-1448](#) [76-1556](#) [76-019](#) [76-024](#) [76-1568](#) [21-670](#) [72-14400](#) [72-13762](#) [72-13826](#) [72-13832](#) [72-13888](#) [72-13942](#) [72-14008](#) [72-14014](#) [72-14048](#) [72-14148](#) [72-14230](#) [72-17175](#) [72-2655](#) [72-7615](#) [76-1446](#) [76-022](#)