

This document was generated on 10/02/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0760105327

Status: Active

Overview: iPass Connector System

Description: 0.80mm Pitch iPass I/O Connector Shell, Vertical, Through Hole 1.96mm, 68 Circuits,

Dual Key

Documents:

Drawing (PDF) RoHS Certificate of Compliance (PDF)

Packaging Specification PK-76010-002 (PDF)

General

Product Family I/O Connectors

Series <u>76010</u>

Application Wire-to-Board Component Type Shell Body

Overview <u>iPass Connector System</u>

Product Name iPass
Type N/A

UPC 822350748834

Physical

Boot Color N/A Circuits (Loaded) N/A Circuits (maximum) 68 Circuits Detail 68 Durability (mating cycles max) 25 Gender N/A Keying to Mating Part Yes Lock to Mating Part None

Material - Metal Copper-Nickel-Zinc

Material - Plating Mating N/A 2.798/g Net Weight Number of Rows Orientation Vertical PC Tail Length 1.96mm **PCB** Locator No **PCB** Retention Yes Packaging Type Tray Panel Mount N/A Pitch - Mating Interface N/A Polarized to Mating Part N/A Polarized to PCB Yes Surface Mount Compatible (SMC) N/A

Temperature Range - Operating -40° to +80°C
Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire Size AWG N/A

Electrical

Current - Maximum per Contact

Grounding to Panel

Shield Type

Shielded


Yes

Voltage - Maximum

N/A

Solder Process Data

Duration at Max. Process Temperature (seconds) 015



EU ELV Not Relevant

Not itcicvant

EU RoHS China RoHS Compliant

REACH SVHC Not Contained Per -ED/61/2018 (27 June 2018)

Halogen-Free
Status
Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
ROHS Phthalates Not Contained

Search Parts in this Series

76010 Series

Mates With

79575 iPass Internal Cable, 74563 iPass Mini-SAS Internal Cable, 79576 iPass 36 Circuit-SATA Fanout Cable, 74573 iPass 36 Circuit RA-SATA Cable, 79536 iPass 36 Circuit SATA Cable, 74562 iPass 36 Circuit Right Angle

Use With

75577 0.80mm Pitch iPass I/O Connector

SMC&WAVE

Lead-freeProcess Capability
Max. Cycles at Max. Process Temperature 001 Process Temperature max. C 260

Material Info

Reference - Drawing Numbers Packaging Specification PK-76010-002 Sales Drawing SD-76010-002

This document was generated on 10/02/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 1410191-1 1410337-1 1410368-3 1410964-2 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0736440217 1-1393708-5 72388-0021LF 73774-1000 532939-1 5-531355-3 5532901-3 85838-180LF HM1S43TRR460H6PLF 0760205010 1-966831-4 3-1469268-7 77427-121LF