

EL-EnviroPad-TC

Thermometer with Inbuilt Data Logging & Graphing

ORDERING INFORMATION

Thermometer with
Inbuilt Data Logging
& Graphing

EL-EnviroPad-TC

FEATURES

- Temperature °C or °F
- Supplied with K type probe
- Graphing
- Two modes: 'Data Logging' or 'Spot Measurement'
- High & Low Alarms
- 2.8" colour touch screen
- Compatible with thermocouples type J, K, N & T
- Downloadable data via USB
- Internal rechargeable lithium polymer battery
- Date & time function
- Sounder
- Removable protective boot for increased durability



This robust easy to use handheld device takes and records temperature readings via the attached k-type probe that is supplied with the unit. A large touch screen, colour display indicates temperature, maximum and minimum readings and will produce a graph of the data.

It has two functions 'Data Logging' and 'Spot Measurement':

1. When in 'Data Logging' mode it can be set up and left to take temperature readings at pre-determined intervals for a desired length of time. All readings are saved to a file with a date and time stamp in CSV format for up to 65,536 readings.
2. When in 'Spot Measurement' mode the unit can be used as a thermometer to capture one-off temperature readings displayed on screen. This can be repeated for up to 65,536 readings per file.

This data can then be downloaded to PC via a USB connection and opened with Microsoft Excel® or our EasyLog software which is available for free from www.easylogusb.com.

The unit is compatible with any J, K, N and T type thermocouple probes. The protective boot can be removed for cleaning and is dishwasher safe.

Specifications	Minimum	Typical	Maximum	Unit
USB supply voltage	4.5v	-	5.5v	V d.c.
Internal resolution	-	0.1	-	°C
Data recording capacity (per recording)	-	-	65536	readings
Hand unit operating temperature range	0 (+32)	-	+50 (+122)	°C (°F)
Operating time (on a single charge)	8	24*	**	hrs
Displayable temperature (dependant on probe)	-100	-80 to +1200	+9999	°C
Storage capacity	-	-	100	files

* Typical use: 1min recording rate & power-save

** Depends on recording settings

Warning - Do not exceed operating temperatures



www.lascarelectronics.com



EL-EnviroPad-TC

Thermometer with Inbuilt Data Logging & Graphing

HARDWARE

UNIT

- Battery: rechargeable via USB connection
- LCD: colour TFT touch-screen
- Integrated memory for logged data
- Single front-panel push-button used for power-switch. Single press=ON, press & hold=OFF.
- 1x thermocouple connector (top of unit)
- 1x micro USB Type B (bottom of unit) for connection of unit to PC via USB cable supplied.

PROBE

- Thermocouple probe: class 1 tolerance, 316 stainless steel probe
- Sealed to IP66
- Themocouple Type: K

Specifications	Minimum	Typical	Maximum	Unit
Probe Temperature Accuracy	-	+/- 1.5	-	°C
Probe Temperature Range*	-180	-	+1300	°C
Handle Temperature Range	-10	-	+125	°C

* Short term measurement

N.B. Any of the above hardware specifications may change without prior warning if new/suitable alternatives become available.

EL-EnviroPad-TC

Thermometer with Inbuilt Data Logging & Graphing

DIMENSIONS

All dimensions in mm (inches)



Module House
Whiteparish, Salisbury
Wiltshire SP5 2SJ
UK
T +44 (1794) 884567
F +44 (1794) 884616
E sales@lascar.co.uk

4258 West 12th Street
Erie
PA 16505
USA
T +1 (814) 835 0621
F +1 (814) 838 8141
E us-sales@lascarelectronics.com

8th Floor, China Aerospace Centre
143 Hoi Bun Road
Kwun Tong, Kowloon
HONG KONG
T +852 2797 3219
F +852 2343 6187
E saleshk@lascar.com.hk



www.lascarelectronics.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Lascar](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)