


Item no.: 750-514
 Product description: 2-CHANNEL RELAY OUTPUT MODULE AC 125 V, DC 30 V



Produkt kann von Bild abweichen / product may differ

Packing unit 1 piece

RoHS compliant

Product group	15 (I/O System)
Number of outputs	2 CHANGEOVER CONTACTS (SPDT)
Current consumption typ (internal)	70 mA
Switching voltage	AC 125 V / DC 30 V
Switching power	62.5 VA / 30 W
Switching current (max)	AC 0.5 A / DC 1 A
Switching current (min)	DC 0,01mA / 10mV
Max. switching frequency	20 / min
Pull-in time max.	4 ms
Drop-out time max.	4 ms
Contact material	Silver alloy, gold-plated
Mechanical life	1 x 10 ⁸ switching operations
Electrical life	2 x 10 ⁵ (AC 0.5 A / 125 V) 5x 10 ⁵ (DC 1 A / 30 V)
Isolation	1.5 kV EFF. (FIELD/SYSTEM), 2.5 kV RATED SURGE VOLTAGE; OVERVOLTAGE CATEGORY III
Internal data width (Bit)	2 Bit
Operating temperature	0 °C ... + 55 °C
Storage temperature	-25 °C ... +85 °C

Relative air humidity	95 %
Vibration resistance	acc. IEC 60068-2-6
Shock resistance	acc. IEC 60068-2-27
Degree of protection	IP 20
Conformity marking	CE



Approvals	ATEX
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP® CONNECTION
Weight	49.5 g
Color	light gray
Height	64 mm
Height	2.52 in
Width	12 mm
Width	0.472 in
Depth	100 mm
Depth	3.937 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
750-514	ABS	03-HG374860/3-PDA			
750-514	BSH	Bescheinigung Nr. 467			
750-514	DNV	A-12306			
750-514	GL	26 898 - 05 HH			
750-514	KEMA	01 ATEX 1024 X			
750-514	PRS	TE/1720/880590/08			
750-514	Rina	ELE153207CS001			
750-514	UL	E175199 Sec.1			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [wago manufacturer](#):

Other Similar products are found below :

[750-460](#) [231-118/026-000](#) [231-303/026-000](#) [231-620/019-000](#) [257-403](#) [280-438](#) [280-831](#) [284-624](#) [210-111](#) [231-303/037-000](#) [231-446/001-000_NR](#) [232-216/026-000](#) [234-510](#) [264-726](#) [280-339](#) [0283-0671](#) [830-800/000-305](#) [750-512](#) [750-455](#) [51251782](#) [286-312](#) [713-1428/107-000](#) [731-138/048-000](#) [750-459](#) [750-517](#) [750-602](#) [793-3505](#) [826-172](#) [859-304](#) [280-335](#) [231-535/001-000](#) [2604-1105](#) [2604-1106](#) [2604-1504](#) [2606-1103/020-000](#) [2624-1103](#) [2626-3103/020-000](#) [821-104](#) [713-1107](#) [852-1411](#) [2106-1307](#) [2116-5307](#) [832-1205](#) [832-3604](#) [2009-110](#) [281-512/281-501](#) [286-336](#) [750-421](#) [750-838](#) [753-559](#)