

## Datasheet for part number MDSM-15PE-Z10-VR22

	Our Catalog Part Number: MDSM-15PE-Z10-VR22 Our Global Manufacturing Part Number: 121661-1042		
	Brand: Cannon Product Category: D Sub Product Line: D Sub Series: MDSM		

Product Datasheet	
Series	Micro MDSM
Mating Cycles	500
Layout	15 contacts
Gender	Pin
Termination Type	Solder pin 90°, spacing 1,27 x 2,54 mm, with rivet nut and grounding tab
Mounting Methode	Screw for wall thickness 1,5 mm
Packaging	22 pieces in tube packaging
Insulator	Thermoplast, UL94V-0
Contact guiding plate	PA, high temperature resistant
Shell	Steel, tinned and nickel plated
Contact Type	Copper alloy
Contact Finish	Gold over PdNi
Contact Termination Area	Tin
Wire size	AWG 26 - 28
Insulation diameter	0.95 mm max
Contact spacing	1.27 mm
Temperature range	-55°/+125°
Current rating	2.5 A / 25°C
Test voltage	350 Vrms
Contact resistance	35 mOhm max
Insulation resistance	500 mOhm min

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for itt manufacturer:

Other Similar products are found below :

MDM-9SL1B NEM-QTHSSB-68PGNS-B MJSR-34PL61 096520-0863 096520-0927 153205-3053 096522-0534 097391-0281 MDM-37PCBR-F222 CA3108E14S-5PBA176A232 MJSR-42PH003 MDM-51PCBRP-L56 CV3456L28-15P KPSE06F20-41SA206F0 CB2-18-3SCA232 MS3106E22-14P 252-7689-001 097414-0074 130680-0000 CA3101E10SL-4SF80DN CA3101E10SL-4PBA176F42 053513-4377 MS3100F14S-7S 051212-0001 MS3101E181SW 980-8001-545 CAR3102A20-27SX 024253-0025 024265-0001 024270-0015 024273-0043 024288-0001 M24308/24-21F CT1F22-7SS CT2-20-23SWS CT2-20-23SXS CT2-36-10PCAU CT6-24-11PSA206 CT6F36-10PCA152 CT6F9767-14-4-14S-5PC CT6T9767-14-4-14SA7SS D38999/20FG16PA-LC - D38999/26JH21PB-LC MD1-21PS MDM-15PH001B-A174 MDM-15PH003B-A174 MDM-21SCBR-A174 MDM-21SCBRP-A174 MDM-21SH003B MDM25PH003BF222