

## CLIPPER FOOTSWITCH



Clipper Footswitch



Clipper Wide Treadle Footswitch

### Environmental Ratings:

EN 60529 Degree of Protection IP20

### Key Benefits

The rugged, long life Clipper foot switch models have proved themselves in the field over many years of usage. All maintained models offer "Push On-Push Off" action that insures long trouble-free performance. The wide treadle models offer a large seven inch target for the operator's foot. Cast iron housing. Nonskid base pad. Complete with adjustable strain relief connector. Black finish.

Size: 4-1/2" x 3-1/2" x 1-1/2"  
Weight: 2-1/4 lbs.

The CLIPPER TWIN consists of two SPDT or two DPDT foot switches mounted on a heavy steel base plate with nonskid pad. Divider bar between pedals helps prevent accidental operation of both pedals at one time. A tube between the two foot switches conceals all internal wiring between them. A conduit opening with strain relief connector is provided in the right foot switch.

Size: 8-3/8" x 4-1/2" x 1-1/2"  
Weight: 5 lbs.

Model 638-S features a cast aluminum housing painted Alert Orange with a splash resistant interior switch.






[Request A Quote](#)

### SPECIFICATIONS

(Special variations are available to the O.E.M. on special order on the models listed below)

**⚠ WARNING**

CATALOG NUMBER		DESCRIPTION	CIRCUIT	FORM	ELECTRICAL RATINGS
REGULAR TREADLE	WIDE TREADLE				
632-S	642-S	Momentary	SPDT	C	20 A 125-250 VAC 1 H.P. 125-250 VAC
632-SC3*		Momentary	SPST Wired N.O.	A	15 A 125 VAC 3/4 H.P. 125 VAC
633-S	643-S	Momentary	SPDT DB±	Z	20 A 125-250 VAC 3/4 H.P. 125 VAC 1 H.P. 250 VAC
635-S	645-S	Momentary	DPDT	C	15 A 125 VAC 10 A 250 VAC 1/2 H.P. 125-250 VAC
636-S	646-S	Two Stage Momentary	Each Stage SPDT	C	15 A 125 VAC 10 A 250 VAC 1/2 H.P. 125-250 VAC
632-DA	642-DA	Maintained	SPDT	C	20 A 125-250 VAC 1 H.P. 125-250 VAC

	634-DA	Maintained	DPDT	C	10 A 125-250 VAC 1/8 H.P. 125 VAC 1/4 H.P. 250 VAC
	<b>TWIN 632-S</b>	Momentary	Each Side SPDT	C	20 A 125-250 VAC 1 H.P. 125-250 VAC
	TWIN 635-S	Momentary	Each Side DPDT	C	15 A 125 VAC 10 A 250 VAC 1/2 H.P. 125-250 VAC
	638-S	Momentary	SPDT	C	10 A 125-250 VAC 1/2 H.P. 125-250 VAC
	638-SC38** (IP21)	Momentary	SPST Wired N.O.	A	10 A 125-250 VAC 1/2 H.P. 125-250 VAC

**Model 638-S features a cast aluminum housing painted Alert Orange with a splash resistant interior switch.**

**\*Supplied with 8 ft. 14/3 cord and 3 prong series plug. Green lead grounded.**

**\*\*Supplied with 8 ft. 16/3 cord, wired N.O. with green lead grounded.**

**±DB Double Break models must be wired to equal voltage sources and the same polarity. The loads should be on the same sides of the line.**

**BOLD COPY INDICATES STOCK ITEM**

[Home](#) | [About](#) | [Products](#) | [Catalog](#) | [Int'l Distributors](#) | [Glossary](#) | [Support](#) | [Representative](#) | [ISO-9001](#) | [Literature](#) | [Press](#) | [Shows](#) | [Directions](#) | [Contact](#)

LINEMASTER Switch Corporation · 29 Plaine Hill Road · POB 238 · Woodstock, CT 06281-0238 · USA

Tel: 860.974.1000 Fax: 860.974.0691 or Toll-Free Fax 800.974.3668 (USA Only)

© Copyright  
Linemaster Switch Corporation  
2005

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [9V Battery Snaps & Contacts](#) category:*

*Click to view products by [Linemaster](#) manufacturer:*

Other Similar products are found below :

[139B](#) [173P](#) [266](#) [491-SC36](#) [642-S](#) [1295](#) [12BC2202-GR](#) [2238](#) [2241](#) [2242](#) [2243](#) [227](#) [236](#) [237](#) [2410.0301-01](#) [262](#) [270](#) [271](#) [121-0626/I-GR](#)  
[121-0426/IM-GR](#) [121-0626/T-GR](#) [121-0826/T-GR](#) [121-1026/I-GR](#) [12BH617T-GR](#) [123-5025-GR](#) [12BC269-GR](#) [12BH615D-GR](#) [121-](#)  
[0624/O-GR](#) [GEM-V36](#) [531-SWHOX](#) [971-SB](#) [T-91-SC3](#) [632-DA](#) [634-DA](#) [636-S](#) [635-S](#) [632S TWIN DIVIDER](#) [3C-30A2-S](#) [3B-30A2-S](#)  
[534-SS](#) [491-S](#) [L-2-S](#) [971-SO](#) [972-S](#) [606-1300-011](#) [606-1800-012](#) [616-1800-247](#) [6254-OB](#) [6289-PP](#) [6289-CC](#)