


PROFESSIONAL LED INDICATORS - Ø 13mm Mounting





- Low profile styling
- Flying lead terminations available
- Sealed to IP67





MLQ = 10



Ordering Information & Typical Technical Characteristics (Ta = 25°C)

Mean Time Between Failure = 100,000 Hours. Luminous intensity figures refer to the unmodified discrete LED.

PART NUMBER	COLOUR		LENS	VOLTAGE DC Vf@20mA	CURRENT DC lopr	LUMINOUS INTENSITY Iv@20mA	WAVE LENGTH p	VIEWING ANGLE	OPERATING TEMP Topr	STORAGE TEMP Tstg
HIGH INTENSITY										
528-501-21	Red	0		12	20	2750	660			
528-521-21	Yellow	0		12	20	4500	590			
528-532-21	Green	0		12	20	6000	525			
528-930-21	Blue			12	20	2000	470			
528-997-21	White	0	Coloured Diffused	12	20	3000	•	Wide	-40~+85	-50~ + 100
528-501-22	Red	0		24	20	2750	660			
528-521-22	Yellow	0		24	20	4500	590			
528-532-22	Green	0	1	24	20	6000	525			
528-930-22	Blue			24	20	2000	470			
528-997-22	White	0		24	20	3000	•			
UNITS				Vdc	mA	mcd	nm		°C	°C

• = Typical emission colour: x=0.31, y=0.32. Colour temperature 8000K. Intensities (Iv) and colour shades of white (x,y co-ordinates) may vary between LEDs within a batch.

Please note - This product is also available at 28 and 48Vdc, 110 and 230Vac. Please contact our Sales department for further details.

Making Light Work For You! Making Light



● ISO 9001: 1994 APPROVED

Telephone +44 (0)1229 582430 • Fax: +44 (0)1229 585155 • email: sales@marl.co.uk • website: www.marl.co.uk • website: www.marl.co.uk • website: www.marl.co.uk



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Panel Mount Indicators category:

Click to view products by Marl manufacturer:

Other Similar products are found below:

607-1312-310F 607-3232-140F 6091M1-24V 6091M5-24V 6091M7-24V 821-0331-503 FL2870C8R FL2950WL7B FL589WL8R

Q6P3BXXB12E H8630FBBA3 MPC5ADW6.0 DX1091GN NL177WL3G NL276C3G NL2950BWL3G NL2950CWL2R NL589WL2R

NL67C3G NL67C3R 2191L1-12V PB22SIOL0RG PB22SPPM41R PB22SPPM61R LE177C5B LH1048BSWL3702 LH1048BWL3702

LH382A LHM62B SSI-LXH387USBD-150 SSI-LXH9ZIC40587 SSP-LXS110818BA FL2950BWL7R FL2950WL7R FL2951WL8G

FL2951WL8R FL589C7R FL67C7R FL67WL8G 2191QU7-24V 2191U1-12V 2191U5-12V 2191U5-6V 2191U7-12V 249-4167-3734-504F Q6P5BXXG02E 3990A7 5110F3-12V MPC5BCW18.0 556-1237-801F