

SEV SERIES

85°C Standard, Lead Free Reflow Soldering

◆FEATURES

- Case Dia $\phi 3 \sim \phi 18$ mm
- RoHS compliance.
- Lead free reflow soldering is available.
- Available for high density mounting.





◆SPECIFICATIONS

Items	Characteristics																																								
Category Temperature Range	-40~+85°C																																								
Rated Voltage Range	4~100Vdc																																								
Capacitance Tolerance	±20%(20°C,120Hz)																																								
Leakage Current(MAX)	I=0.01CV or 3 μ A whichever is greater.(After 2 minutes application of rated voltage) I=Leakage Current(μ A) C=Capacitance(μ F) V=Rated Voltage(Vdc)																																								
(tan δ) Dissipation Factor(MAX)	<table border="1"> <thead> <tr> <th>Rated Voltage (Vdc)</th> <th>4</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> </tr> </thead> <tbody> <tr> <td>$\phi 4, \phi 5, \phi 6.3 \times 5.5$</td> <td>0.40</td> <td>0.26</td> <td>0.22</td> <td>0.18</td> <td>0.16</td> <td>0.13</td> <td>0.12</td> <td>—</td> <td>—</td> </tr> <tr> <td>$\phi 6.3 \times 8, \phi 8 \sim \phi 12.5$</td> <td>0.50</td> <td>0.35</td> <td>0.26</td> <td>0.20</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.12</td> <td>0.10</td> </tr> <tr> <td>$\phi 16, \phi 18$</td> <td>—</td> <td>0.48</td> <td>0.34</td> <td>0.24</td> <td>0.18</td> <td>0.14</td> <td>0.12</td> <td>0.12</td> <td>0.10</td> </tr> </tbody> </table> (20°C,120Hz) When rated capacitance is over 1000 μ F, tan δ shall be added 0.02 to the listed value with increase of every 1000 μ F.	Rated Voltage (Vdc)	4	6.3	10	16	25	35	50	63	100	$\phi 4, \phi 5, \phi 6.3 \times 5.5$	0.40	0.26	0.22	0.18	0.16	0.13	0.12	—	—	$\phi 6.3 \times 8, \phi 8 \sim \phi 12.5$	0.50	0.35	0.26	0.20	0.16	0.14	0.12	0.12	0.10	$\phi 16, \phi 18$	—	0.48	0.34	0.24	0.18	0.14	0.12	0.12	0.10
Rated Voltage (Vdc)	4	6.3	10	16	25	35	50	63	100																																
$\phi 4, \phi 5, \phi 6.3 \times 5.5$	0.40	0.26	0.22	0.18	0.16	0.13	0.12	—	—																																
$\phi 6.3 \times 8, \phi 8 \sim \phi 12.5$	0.50	0.35	0.26	0.20	0.16	0.14	0.12	0.12	0.10																																
$\phi 16, \phi 18$	—	0.48	0.34	0.24	0.18	0.14	0.12	0.12	0.10																																
Endurance	After applying rated voltage with rated ripple current for 2000 hrs at 85°C, the capacitors shall meet the following requirements. <table border="1"> <tr> <td>Capacitance Change</td> <td>Within ±25% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table>	Capacitance Change	Within ±25% of the initial value.	Dissipation Factor	Not more than 200% of the specified value.	Leakage Current	Not more than the specified value.																																		
Capacitance Change	Within ±25% of the initial value.																																								
Dissipation Factor	Not more than 200% of the specified value.																																								
Leakage Current	Not more than the specified value.																																								
Low Temperature Stability Impedance Ratio(MAX)	<table border="1"> <thead> <tr> <th>Rated Voltage (Vdc)</th> <th>4</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> </tr> </thead> <tbody> <tr> <td>Z(-25°C)/Z(20°C)</td> <td>7</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>Z(-40°C)/Z(20°C)</td> <td>15</td> <td>8</td> <td>8</td> <td>4</td> <td>4</td> <td>3</td> <td>3</td> <td>5</td> <td>5</td> </tr> </tbody> </table> (120Hz)	Rated Voltage (Vdc)	4	6.3	10	16	25	35	50	63	100	Z(-25°C)/Z(20°C)	7	4	3	2	2	2	2	2	2	Z(-40°C)/Z(20°C)	15	8	8	4	4	3	3	5	5										
Rated Voltage (Vdc)	4	6.3	10	16	25	35	50	63	100																																
Z(-25°C)/Z(20°C)	7	4	3	2	2	2	2	2	2																																
Z(-40°C)/Z(20°C)	15	8	8	4	4	3	3	5	5																																

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency (Hz)	60(50)	120	500	1k	10k \leq
0.47~1 μ F	0.50	1.00	1.20	1.30	1.50
2.2~4.7 μ F	0.65	1.00	1.20	1.30	1.50
10~47 μ F	0.80	1.00	1.20	1.30	1.50
100~1000 μ F	0.80	1.00	1.10	1.15	1.20
2200~10000 μ F	0.80	1.00	1.05	1.10	1.15

◆MARKING



※ Voltage code

Rated Voltage (Vdc)	6.3	10	16	25	35	50	63	100
Rated Voltage code	0J	1A	1C	1E	1V	1H	1J	2A

◆PART NUMBER



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - SMD category](#):

Click to view products by [Rubycon manufacturer](#):

Other Similar products are found below :

[GA0402A270FXBAC31G](#) [RVB-50V330MG10UQ-R](#) [RVJ-50V101MH10U-R](#) [RVZ-35V151MH10U-R2](#) [RC0J226M04005VR](#)
[RC0J476M05005VR](#) [RC1A227M08010VR](#) [RC1C226M05005VR](#) [RC1C476M6L005VR](#) [RC1E107M6L07KVR](#) [RC1E336M6L005VR](#)
[RC1H106M6L005VR](#) [RC1H475M05005VR](#) [RC1V227M10010VR](#) [RC1V476M6L006VR](#) [50SEV1M4X5.5](#) [TYEH1A336E55MTR](#)
[TYEH1H106F55MTR](#) [TYEH1V106E55MTR](#) [35SEV47M6.3X8](#) [35SGV220M10X10.5](#) [VES2R2M1HTR-0405](#) [VZH102M1ATR-1010](#)
[50SEV10M6.3X5.5](#) [50SGV1M4X6.1](#) [SC1C476M05005VR](#) [SC1E107M0806BVR](#) [SC1E227M08010VR](#) [SC1H106M05005VR](#)
[SC1H106M6L005VR](#) [SC1H227M10010VR](#) [SC1H335M04005VR](#) [CE4.7/50-SMD](#) [VEJ4R7M1VTR-0406](#) [VZH331M1ETR-0810](#)
[VES101M1CTR-0605](#) [TYEH1H475E55MTR](#) [6.3SEV22M4X5.5](#) [6.3SEV47M4X5.5](#) [EEEFK1H151GP](#) [EEEFK1A681GP](#) [EEE0GA471XP](#)
[EEEFK1V151GP](#) [RC1V107M6L07KVR](#) [VZH101M1VTR-0810](#) [VE010M1HTR-0405](#) [GYA1V151MCQ1GS](#) [EEH-ZC1J680P](#) [EEH-](#)
[ZK1V181P](#) [GYA1V271MCQ1GS](#)