Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

AX102430 Faceplates and Panels - MediaFlex Faceplate Kit KeyConnect 6-Port, Flush, Single-Gang





-



For more Information please call

1-800-Belden1



General Description:

MediaFlex Faceplate Kit KeyConnect 6-Port, Flush, Single-Gang

sage (Overall)	
Suitable Applications:	 Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800,3600, 2400 and 1200.
Related Parts:	 Compatible with REVConnect Jacks (UTP & STP), KeyConnect Jacks (UTP) and Keyconnect Multimedia Modules. See notes if using KeyConnect Shielded (STP) Jacks.
nysical Characteristics (Connectivity)	
apacity	
Max. Capacity:	6 ports
ccess	
Front Connection:	Flush
imensions Dimensions:	
Height (in.) Width (in.) Depth (in.)	
4.500 3.020 0.455	
laterials Materials:	
Description Material	
Faceplate Plastic - UL94V-0	
Insert Plastic - UL94V-0	
olor	
Color:	Almond
leight	
Weight:	0.100 lbs.
ncluded Parts	
Included Parts:	Windows, paper, 6-32 screws, 2-port insert, 2U blank insert, blank, installation guide
ackaging	
Packaging:	Individually packaged in a suitable plastic bag
echanical Characteristics (Connectivity)	
Footprint/Type:	KeyConnect
Connector/Hardware Retention:	20 lbs.
Storage Temperature Range:	-40°C To +70°C
Installation Temperature Range:	-10°C To +60°C
Operating Temperature Range:	-10°C To +60°C
oplicable Specifications and Agency Complia	ance (Overall)
pplicable Standards & Environmental Programs	
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
MII Order #39 (China RoHS):	EUP 50
Safety Listing:	ACA, c(UL)us Listed
uitability	
a second s	



ENGLISH MEASUREMENT VERSION

AX102430 Faceplates and Panels - MediaFlex Faceplate Kit KeyConnect 6-Port, Flush, Single-Gang

Transmission Characteristics (Connectivity)

Notes (Overall)

.

Notes: Please contact Tech Support if using Shielded KeyConnect jacks (AX104562, AX104595, AX104596) for compatibility verification.

duct Family art Numbers:					
Description	Gray	Almond	Elec White	Black	lvory
MediaFlex Faceplate Kit KeyConnect Single-Gang 2-Port Flush	AX104493	AX104494	AX104495	AX104496	AX10577
MediaFlex Faceplate Kit KeyConnect Single-Gang 4-Port Flush	AX104485	AX102428	AX102429	AX104489	AX10577
MediaFlex Faceplate Kit KeyConnect Single-Gang 6-Port Flush	AX104486	AX102430	AX102431	AX104490	AX10577
MediaFlex Faceplate Kit KeyConnect Single-Gang 2-Port Angled	AX104497	AX104498	AX104499	AX104500	AX10578
MediaFlex Faceplate Kit KeyConnect Single-Gang 4-Port Angled	AX104487	AX102432	AX102433	AX104491	AX10578
MediaFlex Faceplate Kit KeyConnect Double-Gang 6-Port Flush	AX105769	AX102523	AX102524	AX105770	AX10578
MediaFlex Faceplate Kit KeyConnect Double-Gang 8-Port Flush	AX105771	AX102520	AX102520	AX105772	AX10578
MediaFlex Faceplate Kit KeyConnect Double-Gang 12-Port Flush	AX104488	AX102434	AX102435	AX104492	AX10578
MediaFlex Faceplate Kit KeyConnect Double-Gang 6-Port Angled	AX105773	AX102521	AX102522	AX105774	AX10578
MediaFlex Faceplate Kit KeyConnect Double-Gang 8-Port Angled	AX105775	AX102436	AX102437	AX105776	AX10578

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX102430	1 EA	0.102 LB			KCONN MFLEX FP KIT 6-P ALM

Revision Number: 0 Revision Date: 08-16-2017

© 2017 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities are protable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Ducting category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

66200A-10 CVED32VEPG CVED40VEPG F512D5-5F140Y F512D5-5F200Y F512D5-5F26Y F512D5-5F30Y F512D5-5F33Y F512D5-5F34Y F512D5-5F45Y F512D5-5F50Y F512D5-5F54Y F512D5-5F66Y F612D5-5F100Y F912D5-5F11Y F912D5-5F170Y F912D5-5F175Y F912D5-5F230Y F912D5-5F300Y F912D5-5F55Y F912D5-5F66Y F912D5-5F63Y F912D5-5F6Y F912D5-5F75Y F912D5-5F85Y F912D5-5F86Y F912D5-5F88Y F912D5-5F96Y FAP0047WBLMTP FAP12WBRDRDDLCZ FAP12WDYLYLDLCZ FAP12WEORORDLCZ FAP6WEORORDLCZ FAP6WFDBDBDLCZ FAP8WEORORDLCZ FCE2UWCL 802I-ICSP FJQADH FJQFXT FX12D5-5F103Y FX12D5-5F112Y FX12D5-5F116Y FX12D5-5F12Y FX12D5-5F153Y FX12D5-5F156Y FX12D5-5F167Y FX12D5-5F185Y FX12D5-5F188Y FX12D5-5F189Y FX12D5-5F194Y