



RECOMMENDED PC BOARD PAD PATTERN
0.20[.008] THICK STENCIL

		106.68 [4.200]	53.34 [2.100]	101.6 [4.000]	109.22 [4.300]	80	4-147747-0
		104.14 [4.100]	50.80 [2.000]	99.06 [3.900]	106.68 [4.200]	78	3-147747-9
		101.60 [4.000]	50.80 [2.000]	96.52 [3.800]	104.14 [4.100]	76	3-147747-8
		99.06 [3.900]	48.26 [1.900]	93.98 [3.700]	101.6 [4.000]	74	3-147747-7
		96.52 [3.800]	48.26 [1.900]	91.44 [3.600]	99.06 [3.900]	72	3-147747-6
		93.98 [3.700]	45.72 [1.800]	88.9 [3.500]	96.52 [3.800]	70	3-147747-5
	120mm	88.90 [3.500]		83.82 [3.300]	91.44 [3.600]	68	3-147747-4
		86.36 [3.400]		81.28 [3.200]	88.9 [3.500]	66	3-147747-3
		83.82 [3.300]		78.74 [3.100]	86.36 [3.400]	64	3-147747-2
		81.28 [3.200]		76.2 [3.000]	83.82 [3.300]	62	3-147747-1
		78.74 [3.100]		71.12 [2.900]	81.28 [3.200]	60	3-147747-0
		76.20 [3.000]		71.12 [2.800]	78.74 [3.100]	58	2-147747-9
		71.12 [2.900]		68.58 [2.700]	76.2 [3.000]	56	2-147747-8
		71.12 [2.800]		66.04 [2.600]	71.12 [2.900]	54	2-147747-7
		68.58 [2.700]		63.5 [2.500]	71.12 [2.800]	52	2-147747-6
	88mm	66.04 [2.600]		60.96 [2.400]	68.58 [2.700]	50	2-147747-5
		63.50 [2.500]		58.42 [2.300]	66.04 [2.600]	48	2-147747-4
		60.96 [2.400]		55.88 [2.200]	63.5 [2.500]	46	2-147747-3
		58.42 [2.300]		53.34 [2.100]	60.96 [2.400]	44	2-147747-2
		55.88 [2.200]		50.8 [2.000]	58.42 [2.300]	42	2-147747-1
		53.34 [2.100]		48.26 [1.900]	55.88 [2.200]	40	2-147747-0
		50.80 [2.000]		45.72 [1.800]	53.34 [2.100]	38	1-147747-9
	72mm	48.26 [1.900]		43.18 [1.700]	50.8 [2.000]	36	1-147747-8
		45.72 [1.800]		40.64 [1.600]	48.26 [1.900]	34	1-147747-7
		43.18 [1.700]		38.1 [1.500]	45.72 [1.800]	32	1-147747-6
		40.64 [1.600]		35.56 [1.400]	43.18 [1.700]	30	1-147747-5
		38.10 [1.500]		33.02 [1.300]	40.64 [1.600]	28	1-147747-4
		35.56 [1.400]		30.48 [1.200]	38.1 [1.500]	26	1-147747-3
		33.02 [1.300]		27.94 [1.100]	35.56 [1.400]	24	1-147747-2
		30.48 [1.200]		25.4 [1.000]	33.02 [1.300]	22	1-147747-1
		27.94 [1.100]		22.86 [1.000]	30.48 [1.200]	20	1-147747-0
		25.40 [1.000]		20.32 [1.000]	27.94 [1.100]	18	147747-9
		22.86 [1.000]		17.78 [1.000]	25.4 [1.000]	16	147747-8
		20.32 [1.000]		15.24 [1.000]	22.86 [1.000]	14	147747-7
		17.78 [1.000]		12.7 [1.000]	20.32 [1.000]	12	147747-6
		15.24 [1.000]		10.16 [1.000]	17.78 [1.000]	10	147747-5
		12.70 [1.000]		7.62 [1.000]	15.24 [1.000]	8	147747-4
		10.16 [1.000]		5.08 [1.000]	12.7 [1.000]	6	147747-3
		7.62 [1.000]		2.54 [1.000]	10.16 [1.000]	4	147747-2
	24mm	5.08 [1.000]		-	7.62 [1.000]	2	147747-1
FINISH	EIA TAPE WIDTH	D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0. PLC	± -
1. PLC	± -
2. PLC	± -
3. PLC	± 0.005[.13]
4. PLC	± 0.0005[.013]
ANGLES	± -

MATERIAL: 1

FINISH: 2, 15

STE TE Connectivity

RCPT ASSY, MOD IV, DOUBLE ROW, VERTICAL, DUAL ENTRY, .100X.100 C/L, SURFACE MOUNT, AMPMODU

108-25022

114-25018

SCALE: 6:1

SHEET 1 OF 2

REV H7

- 1 HOUSING: GLASS FILLED, FLAME RETARDANT POLYESTER, BLACK CONTACTS: PHOSPHOR BRONZE. VACUUM COVER: STAINLESS STEEL
- 2 CONTACTS: DUPLEX PLATED- 0.76µm[.000030] GOLD IN CONTACT AREA, 3.81-7.62µm [.000150-.000300] BRIGHT TIN-LEAD ON, LEADS, ALL OVER 1.27µm [.000050] MIN NICKEL.
- 3 DIMENSION APPLIES TO HOUSING CAVITY CENTERLINES ONLY.
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS.
- 5 POINT OF CONTACT DIMENSION.
- 6 MARK PART NUMBER AND DATE CODE IN APPROXIMATE LOCATION SHOWN, EITHER SIDE.
- 7 TOLERANCE IS NON-CUMULATIVE.
- 8 5.5 [.217] MIN TARGET AREA FOR VACUUM PICK-UP COVERS TO BE REMOVED AFTER SOLDERING.
- 9 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 10 NO CENTER HOLD DOWNS
- 11 PACKAGED IN TAPES AND REEL PER EIA 481 SPECIFICATIONS.
- 12 FOR 2 POS, DATE CODE IS STAMPED OPPOSITE SIDE OF TE LOGO.
- 13 TE TRADEMARK AND CSA LOGO ARE MOLDED INTO HOUSING.
- 14 NO PART NUMBER MARKING REQUIRED ON THIS PART.
- 15 CONTACTS: DUPLEX PLATED-0.76µm[.000030] GOLD IN CONTACT AREA, 3.81-7.62µm [.000150-.000300] MATTE TIN ON LEADS, ALL OVER 1.27µm [.000050] MIN NICKEL.
- 16 ROHS 2002/95/EC COMPLIANT

		106.68 [4.200]	53.34 [2.100]	101.6 [4.000]	109.22 [4.300]	80	18	9-147747-0
		104.14 [4.100]	50.8 [2.000]	99.06 [3.900]	106.68 [4.200]	78	18	8-147747-9
		101.6 [4.000]	50.8 [2.000]	96.52 [3.800]	104.14 [4.100]	76	18	8-147747-8
		99.06 [3.900]	48.26 [1.900]	93.98 [3.700]	101.6 [4.000]	74	18	8-147747-7
		96.52 [3.800]	48.26 [1.900]	91.44 [3.600]	99.06 [3.900]	72	18	8-147747-6
		93.98 [3.700]	45.72 [1.800]	88.9 [3.500]	96.52 [3.800]	70	18	8-147747-5
		88.9 [3.500]		83.82 [3.300]	91.44 [3.600]	68	18	8-147747-4
		86.36 [3.400]		81.28 [3.200]	88.9 [3.500]	66	18	8-147747-3
		83.82 [3.300]		78.74 [3.100]	86.36 [3.400]	64	18	8-147747-2
		81.28 [3.200]		76.2 [3.000]	83.82 [3.300]	62	18	8-147747-1
		78.74 [3.100]		71.12 [2.900]	81.28 [3.200]	60	18	8-147747-0
		76.2 [3.000]		71.12 [2.800]	78.74 [3.100]	58	18	7-147747-9
		71.12 [2.900]		68.58 [2.700]	76.2 [3.000]	56	18	7-147747-8
		71.12 [2.800]		66.04 [2.600]	71.12 [2.900]	54	18	7-147747-7
		68.58 [2.700]		63.5 [2.500]	71.12 [2.800]	52	18	7-147747-6
		66.04 [2.600]		60.96 [2.400]	68.58 [2.700]	50	18	7-147747-5
		63.5 [2.500]		58.42 [2.300]	66.04 [2.600]	48	18	7-147747-4
		60.96 [2.400]		55.88 [2.200]	63.5 [2.500]	46	18	7-147747-3
		58.42 [2.300]		53.34 [2.100]	60.96 [2.400]	44	18	7-147747-2
		55.88 [2.200]		50.8 [2.000]	58.42 [2.300]	42	18	7-147747-1
		53.34 [2.100]		48.26 [1.900]	55.88 [2.200]	40	18	7-147747-0
		50.8 [2.000]		45.72 [1.800]	53.34 [2.100]	38	18	6-147747-9
		48.26 [1.900]		43.18 [1.700]	50.8 [2.000]	36	18	6-147747-8
		45.72 [1.800]		40.64 [1.600]	48.26 [1.900]	34	18	6-147747-7
		43.18 [1.700]		38.1 [1.500]	45.72 [1.800]	32	18	6-147747-6
		40.64 [1.600]		35.56 [1.400]	43.18 [1.700]	30	18	6-147747-5
		38.1 [1.500]		33.02 [1.300]	40.64 [1.600]	28	18	6-147747-4
		35.56 [1.400]		30.48 [1.200]	38.1 [1.500]	26	18	6-147747-3
		33.02 [1.300]		27.94 [1.100]	35.56 [1.400]	24	18	6-147747-2
		30.48 [1.200]		25.4 [1.000]	33.02 [1.300]	22	18	6-147747-1
		27.94 [1.100]		22.86 [.900]	30.48 [1.200]	20	18	6-147747-0
		25.4 [1.000]		20.32 [.800]	27.94 [1.100]	18	18	5-147747-9
		22.86 [.900]		17.78 [.700]	25.4 [1.000]	16	18	5-147747-8
		20.32 [.800]		15.24 [.600]	22.86 [.900]	14	18	5-147747-7
		17.78 [.700]		12.7 [.500]	20.32 [.800]	12	18	5-147747-6
		15.24 [.600]		10.16 [.400]	17.78 [.700]	10	18	5-147747-5
		12.7 [.500]		7.62 [.300]	15.24 [.600]	8	18	5-147747-4
		10.16 [.400]		5.08 [.200]	12.7 [.500]	6	18	5-147747-3
		7.62 [.300]		2.54 [.100]	10.16 [.400]	4	18	5-147747-2
		5.08 [.200]		-	7.62 [.300]	2	18	5-147747-1
	FINISH	EIA TAPE WIDTH	D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN M. BINNER 20MAY02	STE TE Connectivity
DIMENSIONS: mm [INCHES]		CHK J. JOLSON 20MAY02	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD J. JOLSON 20MAY02	NAME
0 PLC ± -	1 PLC ± -	RCPT ASSY, MOD IV, DOUBLE ROW, VERTICAL, DUAL ENTRY, .100X.100 C/L, SURFACE MOUNT, AMPMODU	
2 PLC ± -	3 PLC ± 0.005(.13)	PRODUCT SPEC 108-25022	
4 PLC ± 0.0005(.013)	ANGLES ± -	APPLICATION SPEC 114-25018	
MATERIAL 1	FINISH 2 15	SIZE A1	CAGE CODE 00779
CUSTOMER DRAWING		DRAWING NO. 147747	RESTRICTED TO
SCALE 1:1		SHEET 2 OF 2	REV H7

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)